



CONNECTORS

Product Name	Description
ANO 2211-2003	2.4mm Straight Male Solder For IW1401/PLEX-135 Cable Captivated Contact
ANO 2211-2013	2.4mm Straight Male Solder For PLEX-130P Cable Captivated Contact
ANO 2211-2028	2.4mm Straight Male Solder for PLEX-130P Cable, Captivated Contact
ANO 2211-2033	2.4MM Straight Male Solder For UT-085/UT-085C-Form Cable, Captivated Contact
ANO 2211-2044	2.4mm Straight Male Solder for .047 Cable, Solder Direct
ANO 2211-3011-1	2.4mm Straight Male 4 Hole .500" SQ. Flange To Accept .009" Pin Dia., Field Replaceable
ANO 2211-3011-2	2.4mm Straight Male 4 Hole .500" SQ Flange To Accept .012" Pin Dia., Field Replaceable
ANO 2211-3011-3	2.4mm Straight Male 4 Hole .500" SQ. Flange To Accept .020" Pin Dia., Field Replaceable
ANO 2211-3018-1	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3018-2	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3018-3	2.4mm Straight Male 4 Hole .375" SQ. Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3019-1	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .009" Pin Dia, Field Replaceable
ANO 2211-3019-2	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .012" Pin Dia, Field Replaceable
ANO 2211-3019-3	2.4mm Straight Male 2 Hole .625" Long Flange, Accepts .020" Pin Dia, Field Replaceable
ANO 2211-3020-1	2.4mm Straight Male 2 Hole .550" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3020-2	2.4mm Straight Male 2 Hole .550" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3020-3	2.4mm Straight Male 2 Hole .550" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3021-1	2.4mm Straight Male 2 Hole .500" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2211-3021-2	2.4mm Straight Male 2 Hole .500" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2211-3021-3	2.4mm Straight Male 2 Hole .500" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2211-3031	2.4mm Stright Male, 2 Hole Flange .550" Long, Flange, Solder Attachment Pin Terminal
ANO 2211-3053	2.4mm Straight Male 4 Hole Flange With Extended Teflon And Blunt Post
ANO 2212-1046	2.4mm Straight Female 2 Hole Flange Mount, Solder for .034 Cable
ANO 2212-2008	2.4mm Straight Female Solder for IW1401 Cable Captivated Contact
ANO 2212-2016	2.4mm Straight Female Solder For PLEX-130P Cable Captivated Contact
ANO 2212-3005-1	2.4mm Female, 2 Hole .622" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3005-2	2.4mm Female, 2 Hole .622" Long Flange Accept .012" Pin Dia., Field Replaceable



ANO 2212-3005-3	2.4mm Female, 2 Hole .622" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3005-4	2.4mm Female, 2 Hole .622" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3005-5	2.4mm Female, 2 Hole .622" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3006-1	2.4mm Female, 2 Hole .551" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3006-2	2.4mm Female, 2 Hole .551" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3006-3	2.4mm Female, 2 Hole .551" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3006-4	2.4mm Female, 2 Hole .551" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3006-5	2.4mm Female, 2 Hole .551" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3009-1	2.4mm Female, 2 Hole .500" Long Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3009-2	2.4mm Female, 2 Hole .500" Long Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3009-3	2.4mm Female, 2 Hole .500" Long Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3009-4	2.4mm Female, 2 Hole .500" Long Flange Accept .015" Pin Dia., Field Replaceable
ANO 2212-3009-5	2.4mm Female, 2 Hole .500" Long Flange Accept .018" Pin Dia., Field Replaceable
ANO 2212-3012-1	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2212-3012-2	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2212-3012-3	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2212-3012-4	2.4mm Female, 4 Hole .375" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2212-3015	2.4mm Female, 2 Hole Flange, .480" Hole Spacing, Mount Post Contact
ANO 2212-3017-1	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .009" Pin Dia., Field Replaceable
ANO 2212-3017-2	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .012" Pin Dia., Field Replaceable
ANO 2212-3017-3	2.4mm Straight Female 4 Hole .500" SQ. Flange Accept .020" Pin Dia., Field Replaceable
ANO 2212-3024	2.4mm Straight Female 2 Hole .400" Long Flange Mount W/Mouse Hole
ANO 2212-3025	2.4mm Female, 2 Hole .550" Long Flange Mount Post Contact
ANO 2212-3030	2.4mm Female, 4 Hole Flange Mount Post Contact
ANO 2212-3049	2.4mm Female, 4 Hole Flange Mount Post Contact
ANO 2212-3054	2.4mm Female, 2 Hole Flange Mount VRT Launch
ANO 2212-4032	2.4mm Female PCB Mount, ø.012 Pin
ANO 2212-5010-1	2.4mm Female, Rear Thread-In, Accept .020 Pin Dia., Field Replaceable
ANO 2212-5010-2	2.4mm Female, Rear Thread-In, Accept .012 Pin Dia., Field Replaceable



ANO 2212-5010-3	2.4mm Female, Rear Thread-In, Accept .009 Pin Dia., Field Replaceable
ANO 2212-5010-4	2.4mm Female, Rear Thread-In, Accept .009 Pin Dia., Field Replaceable
ANO 2212-5010-5	2.4mm Female, Rear Thread-In, Accept .015 Pin Dia., Field Replaceable
ANO 2212-5010-6	2.4mm Female, Rear Thread-In, Accept .018 Pin Dia., Field Replaceable
ANO 221-A1-H	2.4mm Male End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 221-A1-L	2.4MM Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 221-A2-H	2.4mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.005]
ANO 221-A2-L	2.4mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 221-A3-H	2.4mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 221-A3-L	2.4mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 221-A4-H	2.4mm Male End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 221-A4-L	2.4mm Male End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 222-A1-H	2.4mm Female End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 222-A1-L	2.4mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 222-A2-H	2.4mm Female End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 222-A2-L	2.4mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 222-A3-H	2.4mm Female End Launch Connector Standard Profile, Launch pin ø0.18 [.007]
ANO 222-A3-L	2.4mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 222-A4-H	2.4mm Female End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 222-A4-L	2.4mm Female End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 222-B1	2.4mm Female End Launch Connector Super Small End Launch
ANO 222-C1	2.4mm Female End Launch Connector Super Small End Launch-Wide
ANO 2511-2020	3.5mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 2511-2038	3.5mm Straight Male Solder For .141 Cable, Solder Direct
ANO 2512-2021	3.5mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 2512-2039	3.5mm Straight Female Solder For .141 Cable, Solder Direct
ANO 2512-3040	3.5mm Straight Female, 4 Hole .500 SQ. Flange Mount
ANO 2911-2029	2.92mm Straight Male Solder for UT-085/UT-085C-Form Cable Captivated Contact
ANO 2911-2040	2.92mm Straight Male Solder For UT-085C-LL Cable Captivated Contact



ANO 2911-2070	2.92mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 2911-2088-PT	2.92mm Straight Male Solder for PLEX130P Cable, Captivated Contact
ANO 2911-2091	2.92mm Straight Male Solder For PLEX-140 Cable Captivated Contact
ANO 2911-2095	2.92mm Straight Male Solder For 047SC-2901 Cable
ANO 2911-2097	2.92mm Straight Male Solder For UT-47 Cable, Solder Direct
ANO 2911-2108	2.92mm Straight Male Solder For SR141/RG402 Cable, Captivated Contact
ANO 2911-2120	2.92mm Straight Male Solder for PLEX-090D Cable, Captivated Contact
ANO 2911-2122	2.92mm Straight Male Solder for SR120LL Cable, Captivated Contact
ANO 2911-2129	2.92mm Straight Male Solder for AFLEX-141 Cable, Captivated Contact
ANO 2911-2141	2.92mm Straight Male Solder for AFLEX-086 Cable, Captivated Contact
ANO 2911-3013-1	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3013-2	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3013-3	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3026-1	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3026-2	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3026-3	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2911-3026-4	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .018" Pin Dia., Field Replaceable
ANO 2911-3026-5	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3053-1	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3053-2	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3053-3	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3054-1	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3054-2	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3054-3	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3054-4	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2911-3143	2.92mm Male, 4 Hole Flange Mount Extended Dielectric, Post Contact
ANO 2911-3171	2.92mm Male, 2 Hole Flange Mount, Post Contact
ANO 2911-5056-1	2.92mm Straight Male Thread-in To Accept .009 Pin Dia.
ANO 2911-5056-2	2.92mm Straight Male Thread-in To Accept .012 Pin Dia.



ANO 2911-5056-3	2.92mm Straight Male Thread-in To Accept .020 Pin Dia.
ANO 2911-5064	2.92mm Straight Male Thread-in To Accept .020 Pin Dia.
ANO 2912-1034	2.92mm Straight Bulkhead Female Solder for .086 Cable, Captivated Contact
ANO 2912-1110	2.92mm Straight Bulkhead Female Solder for .086 Cable, Captivated Contact
ANO 2912-1113	2.92mm Straight Bulkhead Female Solder for .141 Cable, Captivated Contact
ANO 2912-1121	2.92mm Straight Female, Bulkhead, Solder for SR120LL Cable
ANO 2912-1145	2.92mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 2912-1149	2.92mm Straight Bulkhead Waterproof Female Solder for PLEX-140 Cable, Captivated Contact
ANO 2912-1152	2.92mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 2912-1158	2.92mm Straight Female, Bulkhead Solder for .141 Cable
ANO 2912-2078	2.92mm Straight Female Solder For IW1501/Plex-140 Cable, Captivated Contact
ANO 2912-2096	2.92mm Straight Female Solder For 047SC-2901 Cable
ANO 2912-2098	2.92mm Straight Female Solder For UT-47 Cable, Solder Direct
ANO 2912-2131	2.92mm Straight Female Solder for AFLEX-141 Cable Captivated Contact
ANO 2912-2164	2.92mm Straight Female, 2 Hole Flange Mount Solder for .086 Cable, Captivated Contact
ANO 2912-3014	2.92mm Straight Female, 4 Holes .374" SQ. Flange Launchers, Field Replaceable
ANO 2912-3019-1	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3019-2	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3019-3	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3050-1	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3050-2	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3050-3	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .015" Pin Dia, Field Replaceable
ANO 2912-3050-4	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3052-1	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3052-2	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3052-3	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3057-1	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .009" Pin Dia., Field Replaceable
ANO 2912-3057-2	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .012" Pin Dia., Field Replaceable
ANO 2912-3057-3	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .020" Pin Dia., Field Replaceable



ANO 2912-3057-4	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .015" Pin Dia., Field Replaceable
ANO 2912-3062-1	2.92mm Female 2 Hole .500" Long Flange Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3062-2	2.92mm Female 2 Hole .500" Long Flange Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3062-3	2.92mm Female 2 Hole .500" Long Flange Accepts .015" Pin Dia, Field Replaceable
ANO 2912-3062-4	2.92mm Female 2 Hole .500" Long Flange Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3063	2.92mm Straight Female, 4 Hole .374" SQ. Flange Launchers
ANO 2912-3065	2.92mm Female, 4 Hole .374" SQ. Flange Mount
ANO 2912-3074	2.92mm Female, 2 Hole Flange, .480" Hole Spacing, Mount Post Contact
ANO 2912-3075	2.92mm Female, 4 Hole .500" SQ. Flange Mount Tab Contact
ANO 2912-3082	2.92mm Female, 4 Hole .500" SQ. Flange Mount Post Contact
ANO 2912-3083	2.92mm Female, 2 Hole .500" Long Flange Mount Post Contact
ANO 2912-3093	2.92mm Female, 2 Hole Flange Mount .400 Hole Spacing, Post Contact
ANO 2912-3117	2.92mm Female, 2 Hole Flange Mount Post Contact
ANO 2912-3142	2.92mm Female, 4 Hole Flange Mount Post Contact
ANO 2912-3147	2.92mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 2912-3155	2.92mm Female, 2 Hole Flange Mount Post Contact
ANO 2912-3166	2.92mm Female, 4 Hole Flange Mount, Post Contact
ANO 2912-3169	2.92mm Straight Female 2 Hole Flange Mount W/ Mouse Hole
ANO 2912-4105	2.92 Female Right Angle End Launch
ANO 2912-4133	2.92mm Female PCB Mount for .042" Board
ANO 2912-5036-1	2.92mm Straight Female Thread-In To Accept .009 Pin Dia
ANO 2912-5036-2	2.92mm Straight Female Thread-In To Accept .012 Pin Dia
ANO 2912-5036-3	2.92mm Straight Female Thread-In To Accept .020 Pin Dia
ANO 2912-5157	2.92mm Straight Female Thread-in, .406 Long, ø.037 Terminal
ANO 291-A1-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 291-A1-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 291-A2-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 291-A2-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 291-A3-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]

ANO 291-A3-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 291-A4-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 291-A4-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 2921-2144	2.92mm Right Angle Male Solder for PLEX-090D Cable, Captivated Contact
ANO 2921-2146	2.92mm Right Angle Male Solder for .086 Cable, Captivated Contact
ANO 2921-2150	2.92mm Right Angle Male Solder for .086 Cable, Captivated Contact
ANO 2921-2161	2.92mm Right Angle Male Solder for .141 Cable, Captivated Contact
ANO 2921-2162	2.92mm Right Angle Male Solder for CXN3507 / IW1501 / PLEX-140 Cable, Captivated Contact
ANO 2921-2167	2.92mm Right Angle Male Solder for CXN3507 / IW1501 / PLEX140 Cable, Captivated Contact
ANO 292-A1-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 292-A1-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 292-A2-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 292-A2-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 292-A3-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 292-A3-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 292-A4-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 292-A4-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 4111-2021	NanoRF Socket Contact Assembly Solder for .047 Cable
ANO 4112-2020	NanoRF Pin Contact Assembly Solder for .086 Cable
ANO 4112-2026	NanoRF Pin Contact Assembly Solder for .047 Cable
ANO 4112-2026-1	NanoRF Pin Contact Assembly Solder for .047 Cable
ANO 6211-2003	1.85MM Straight Male Solder For CXN3506 Cable, Captivated Contact
ANO 6211-2025	1.85mm Straight Male Solder for 047SC-2901 Cable
ANO 6211-2031	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable Captivated Contact
ANO 6211-2038	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable
ANO 6211-3010-1	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .009 Pin Dia, Field Replaceable
ANO 6211-3010-2	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .012 Pin Dia, Field Replaceable
ANO 6211-3011-1	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .009" Pin Dia, Field Replaceable
ANO 6211-3011-2	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .012" Pin Dia, Field Replaceable



ANO 6211-3012-1	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .009" Pin Dia.,Field Replaceable
ANO 6211-3012-2	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .012" Pin Dia.,Field Replaceable
ANO 6211-3044-1	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .009 Dia. Pin, Field Replaceable
ANO 6211-3044-2	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .012 Dia. Pin, Field Replaceable
ANO 6212-2004	1.85mm Straight Female Solder For Cxn3506 Cable, Captivated Contact
ANO 6212-2026	1.85mm Straight Female Solder For 047SC-2901 Cable
ANO 6212-2048	1.85mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 6212-2052	1.85mm Straight Female Solder for .034 Cable, Solder Direct
ANO 6212-3005	1.85mm Straight Female, 2 Hole .625" SQ. Flange, Solder For .047 S/R Cable
ANO 6212-3013-1	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3013-2	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3014-1	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3014-2	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3015-1	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3015-2	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3020-1	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3020-2	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3035-1	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .009 Dia. Pin, Field Replaceable
ANO 6212-3035-2	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .012 Dia. Pin, Field Replaceable
ANO 6212-3037	1.85mm Straight Female, 4 Hole .500 SQ. Flange, Solder For .047 S/R Cable
ANO 6212-3040	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 6212-3041	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 6212-3051	1.85mm Female 2 Hole Flange, Vertical Launch
ANO 621-A1-H	1.85mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 621-A1-L	1.85mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 621-A2-H	1.85mm Male End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 621-A2-L	1.85mm Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 622-A1-H	1.85mm Female End Launch Connector, Launch Pin ø0.18 [.007]
ANO 622-A1-L	1.85mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]



ANO 622-A2-H	1.85mm Female End Launch Connector, Launch Pin ø0.13 [.005]
ANO 622-A2-L	1.85mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 622-C1	1.85mm Female End Launch Connector Super Small End Launch-Wide
ANO 6411-2055	NMD2.92mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 6412-2056	NMD2.92mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 6811-2007	NMD2.4mm Straight Male Solder For PLEX-130P Cable, Captivated Contact
ANO 6812-2008	NMD2.4mm Straight Female Solder For PLEX-130P Cable, Captivated Contact
ANO 6911-2004	NMD1.85mm Straight Male Solder For CXN3506 Cable, Captivated Contact
ANO 6912-2002	NMD1.85mm Straight Female Solder For CXN3506 Cable, Captivated Contact
ANO 7111-2005	NMD3.5mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 7112-2006	NMD3.5mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 7511-2002	MMCX65(MMPX) Straight Angle Male Solder for RG405/.086 Cable
ANO 7521-2001	MMCX65(MMPX) Right Angle Male Solder for RG405/.086 Cable
ANO 7611-2011	1mm Straight Male Solder For .047 Cable
ANO 7611-3004	1mm Straight Male, 2 Hole .400" Long Flange (.009)
ANO 7611-3005	1mm Straight Male, 4 Hole .375" SQ Flange (.009)
ANO 7611-5008	1mm Straight Male, Thread-In (.009)
ANO 7611-5009	1mm Straight Male, Thread-In (.009)
ANO 7612-2010	1mm Straight Female Solder For .047 Cable
ANO 7612-3002	1mm Straight Female, 2 Hole .400" Long Flange (.009)
ANO 7612-3003	1mm Straight Female, 4 Hole .375,ÃÃ SQ. Flange (.009)
ANO 7612-3012	1mm Straight Female, Vertical Launch, Microstrip 2 Hole .400 Long Flange Compression Mount
ANO 7612-5006	1mm Straight Female, Thread-In .375" Long (.009)
ANO 7612-5007	1mm Straight Female, Thread-In .375" Long (.009)
ANO 761-A1-L	1mm Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 762-A1-L	1mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 762-A1-S	1mm Female End Launch Connector Super Small End Launch
ANO 7811-5002-1	SMPS Straight Male Full Detent 4-Port Edge Launch
ANO 7811-5002-2	SMPS Straight Male Smooth Bore 4-Port Edge Launch



ANO 8011-2001	1.35mm Straight Male Solder For .047 Cable
ANO 8011-2003	1.35mm Straight Male Solder for .047 Cable
ANO 8012-2002	1.35mm Straight Female Solder For .047 Cable
ANO 8012-2005	1.35mm Straight Female Solder for .047 Cable
ANO 802-A1-L	1.35mm Female End Launch Connector Low Profile
ANO 9111-2047	SSMA Straight Male Solder for .086 Cable
ANO 9112-3032-1	SSMA Jack Thread-in to Accept .009" Pin Dia
ANO 9112-3032-2	SSMA Jack Thread-in to Accept .012" Pin Dia
ANO 9112-3032-3	SSMA Jack Thread-in to Accept .015" Pin Dia
ANO 9112-3032-4	SSMA Jack Thread-in to Accept .018" Pin Dia
ANO 9112-3032-5	SSMA Jack Thread-in to Accept .020" Pin Dia
ANO 9311-1094	SMP Male Bulkhead Mount For .047 Cable, Full Detent
ANO 9311-1094-1	SMP Male Bulkhead Mount For .047 Cable, Limited Detent
ANO 9311-1094-2	SMP Male Bulkhead Mount For .047 Cable, Smooth Bore
ANO 9311-1120	SMP Male Bulkhead Mount for .047 Cable, Catchers Mitt
ANO 9311-2052-1	SMP Male Full Detent, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing
ANO 9311-2052-2	SMP Male Limited Detent, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing
ANO 9311-2052-3	SMP Male Smooth Bore, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing
ANO 9311-4005-1	SMP Straight Male For PCB Receptacle, Full Detent
ANO 9311-4005-2	SMP Straight Male For PCB Receptacle, Limited Detent
ANO 9311-4005-3	SMP Straight Male For PCB Receptacle, Smooth Bore
ANO 9311-4005-4	SMP Straight Male For PCB Receptacle, Cather's Mitt
ANO 9311-4006-1	SMP Straight Male For PCB Edge Mount, Full Detent
ANO 9311-4006-2	SMP Straight Male For PCB Edge Mount, Limited Detent
ANO 9311-4006-3	SMP Straight Male For PCB Edge Mount, Smooth Bore
ANO 9311-4132-1	SMP-T Straight Full Detent Male for PCB Receptacle
ANO 9311-4132-2	SMP-T Straight Limited Detent Male for PCB Receptacle
ANO 9311-4132-3	SMP-T Straight Smooth Bore Male for PCB Receptacle
ANO 9311-5016-1	SMP Straight Male Full Detent Thread-in Hermetic, .015 Contact



ANO 9311-5016-2	SMP Straight Male Limited Detent Thread-in Hermetic, .015 Contact
ANO 9311-5016-3	SMP Straight Male Smooth Bore Thread-in Hermetic, .015 Contact
ANO 9311-5023	SMP Straight Male Bulkhead Shroud Solder-In Hermetic Seal, Smooth Bore
ANO 9311-5057	SMP Straight Male Bulkhead Solder For .086 Cable
ANO 9311-5069-1	SMP Straight Full Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-2	SMP Straight Limited Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-3	SMP Straight Smooth Bore Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-4	SMP Straight Full Detent Male, Thread-in Receptacle
ANO 9311-5069-5	SMP Straight Limited Detent Male, Thread-in Receptacle
ANO 9311-5069-6	SMP Straight Limited Detent Male, Thread-in Receptacle
ANO 9311-5074	SMP Male Catchers Mitt To Straight Terminal
ANO 9311-5119-1	SMP Straight Full Detent Male Bulkhead Solder for .086 Cable
ANO 9311-5119-2	SMP Straight Limited Detent Male Bulkhead Solder for .086 Cable
ANO 9311-5119-3	SMP Straight Smooth Bore Male Bulkhead Solder for .086 Cable
ANO 9311-5129	SMP Male Full Detent, Thread-in Receptacle
ANO 9311-5137-1	SMP Straight Full Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5137-2	SMP Straight Limited Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5137-3	SMP Straight Smooth Bore Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5137-4	SMP Straight Full Detent Male, Thread-in Receptacle
ANO 9311-5137-5	SMP Straight Limited Detent Male, Thread-in Receptacle
ANO 9311-5137-6	SMP Straight Smooth Bore Male, Thread-in Receptacle
ANO 9311-6009-1	SMP Male Full Detent, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6009-2	SMP Male Limited Detent, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6009-3	SMP Male Smooth Bore, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6010-1	SMP Male Full Detent Hermetic Shroud, Full Shroud Full Body
ANO 9311-6010-2	SMP Male Limited Detent Hermetic Shroud, Full Shroud Full Body
ANO 9311-6010-3	SMP Male Smooth Bore Hermetic Shroud, Full Shroud Full Body
ANO 9311-6063-1	SMP Straight Hermetic Seal Male Full Detent, Solder Type
ANO 9311-6063-2	SMP Straight Hermetic Seal Male Limited Detent, Solder Type



ANO 9311-6063-3	SMP Straight Hermetic Seal Male Smooth Bore, Solder Type
ANO 9311-6065-1	SMP Male Full Detent Hermetic Shroud, Half Shroud Full Body
ANO 9311-6065-2	SMP Male Limited Detent Hermetic Shroud, Half Shroud Full Body
ANO 9311-6065-3	SMP Male Smooth Bore Hermetic Shroud, Half Shroud Full Body
ANO 9311-6090-1	SMP Straight Hermetic Seal Male, Full Detent, Solder Type,
ANO 9311-6090-2	SMP Straight Hermetic Seal Male, Limited Detent , Solder Type,
ANO 9311-6090-3	SMP Straight Hermetic Seal Male, Smooth Bore , Solder Type
ANO 9312-2001	SMP Straight Female Solder For .086 Cable
ANO 9312-2002	SMP Straight Female Solder For .047 Cable
ANO 9312-2011	SMP Straight Female Solder For RG178 Cable
ANO 9312-2082	SMP-QT (SMP QuarterTurn) Straight Female for .086 Cable
ANO 9312-2085	SMP Straight Female Solder for .086 Cable
ANO 9312-2111	SMP Straight Female Solder for .034 Cable
ANO 9312-2114	SMP Straight Female Solder for .027 Cable
ANO 9322-2003	SMP Right Angle Female Solder For .086 Cable
ANO 9322-2004	SMP R/A Female, Solder For .047 S/R Cable
ANO 9322-2012	SMP Right Angle Female Solder For RG178 Cable
ANO 9322-2037	SMP R/A Female Solder For .141 Cable
ANO 9322-2100	SMP Right Angle Female Solder for .086 Cable
ANO 9411-1024-1	SMPM Male Full Detent Snap-in Bulkhead Mount for .047 Cable
ANO 9411-1024-2	SMPM Male Smooth Bore Snap-in Bulkhead Mount for .047 Cable
ANO 9411-2023-1	SMPM Straight Male Solder For .086 Cable, Full Detent
ANO 9411-2023-2	SMPM Straight Male Solder For .086 Cable, Smooth Bore
ANO 9411-2034-1	SMPM Straight Male Bulkhead Solder for .086 Cable, Full Detent
ANO 9411-2034-2	SMPM Straight Male Bulkhead Solder for .086 Cable, Smooth Bore
ANO 9411-2037	SMPM Male Smooth Bore Interface FIT M38999 Size 12 Insert Solder for .086 Cable
ANO 9411-2047	SMPM Straight Male Full Detent 2 Hole Flange Mount Shroud, .350" Hole Spacing
ANO 9411-2049-1	SMPM Straight Full Detent Male Bulkhead Solder for .047 Cable
ANO 9411-2049-2	SMPM Straight Smooth Bore Male Bulkhead Solder for .047 Cable



ANO 9411-3057	SSMP Male Smooth Bore 2 Hole Flange Mount for .086 Cable
ANO 9411-4001-1	SMPM Straight Male for PCB Mount, Full Detent
ANO 9411-4001-2	SMPM Straight Male for PCB Mount, Smooth Bore
ANO 9411-5008-1	SMPM Straight Male Full Detent, Thread-in With ø.012 Contact
ANO 9411-5008-2	SMPM Straight Male Smooth Bore, Thread-in With ø.012 Contact
ANO 9411-5009	SMPM Straight Male Panel Mount Thread-In With ø.024 Contact
ANO 9411-5010	SMPM Straight Male Full Detent Solder-In Hermetic Shroud With ø.012 Contact, .070 Length
ANO 9411-5016-1	SMPM-T Straight Male Full Detent, Thread-In With ø.012 Contact
ANO 9411-5016-2	SMPM-T Straight Male Smooth Bore, Thread-In With ø.012 Contact
ANO 9411-5020-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5020-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5028-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5028-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5030-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5030-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5039-1	SMPM Straight Male Edge Mount, Full Detent
ANO 9411-5039-2	SMPM Straight Male Edge Mount, Smooth Bore
ANO 9411-5041-1	SMPM-T Straight Male For PCB Mount, Full Detent
ANO 9411-5041-2	SMPM-T Straight Male For PCB Mount, Smooth Bore
ANO 9411-5054-1	SMPM-T Straight Full Detent Male, Launcher, (Board Edge Mount)
ANO 9411-5054-2	SMPM-T Straight Smooth Bore Male, Launcher, (Board Edge Mount)
ANO 9411-5055-1	SMPM-T Straight Full Detent Male, Launcher, (Board Edge Mount)
ANO 9411-5055-2	SMPM-T Straight Smooth Bore Male, Launcher, (Board Edge Mount)
ANO 9411-6040-1	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=1.52[.06]
ANO 9411-6040-2	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=2.28[.09]
ANO 9411-6040-3	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=1.52[.06]
ANO 9411-6040-4	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=2.28[.09]
ANO 9411-6051	SMPM Straight Male Screw Type Smooth Bore
ANO 9412-2004	SMPM Straight Female Solder For .047 Cable

ANO 9412-2005	SMPM Straight Female Solder for .086 Cable
ANO 9412-2022	SMPM-T Straight Female Solder For .047 Cable
ANO 9412-2032	SMPM-T Straight Female Solder For .086 Cable
ANO 9412-2038	VITA67.1 Plug-in Contact SMPM Straight Female for .047 Cable
ANO 9412-2043	SMPM Female T-FLEX 405 Cable Fit M38999 Size 12 Insert
ANO 9412-2044	VITA67.3 Plug-in Contact SMPM Straight Female for .086 Cable
ANO 9412-2050	VITA67.1 Plug-in Contact SMPM Straight Female for .086 Cable
ANO 9412-5046	SMPM Straight Female, Panel Mount Thread-in for .020 Dia. Post
ANO 9421-2011-1	SMPM R/A Male Full Detent Solder For .086 Cable
ANO 9421-2011-2	SMPM R/A Male Smooth Bore Solder For .086 Cable
ANO 9421-5042-1	SMPM-T Right Angle Male For PCB Mount, Full Detent
ANO 9421-5042-2	SMPM-T Right Angle Male For PCB Mount, Smooth Bore
ANO 9422-2007	SMPM R/A Female Solder for .047 S/R Cable
ANO 9422-2012	SMPM R/A Female Solder For .086 Cable
ANO 9422-2014	SMPM R/A Female Solder For .047 S/R Cable

ADAPTERS

Product Name	Description
PA2525A	Precision Adapter 3.5mm Male To 3.5mm Male
PA2525B	Precision Adapter 3.5mm Male To 3.5mm Female
PA2525C	Precision Adapter 3.5mm Female To 3.5mm Female
PA2525E	Precision Adapter, 3.5mm Female Bulkhead To 3.5mm Female
PA2525F	Precision Adapter 3.5mm Female To 3.5mm Female 4 Hole Flange
PA6225A	Precision Adapter 1.85mm Male To 3.5mm Male
PA6225B	Precision Adapter 1.85mm Male To 3.5mm Female
PA6225C	Precision Adapter 1.85mm Female To 3.5mm Female
PA6225D	Precision Adapter 1.85mm Female To 3.5mm Male
PA2225A	Precision Adapter 2.4mm Male To 3.5mm Male
PA2225B	Precision Adapter 2.4mm Male To 3.5mm Female
PA2225C	Precision Adapter 2.4mm Female To 3.5mm Female

PA2225D	Precision Adapter 2.4mm Female To 3.5mm Male
PA2925A	Precision Adapter, 2.92mm Male to 3.5mm Male
PA2925B	Precision Adapter, 2.92mm Male To 3.5mm Female
PA2925C	Precision Adapter, 2.92mm Female To 3.5mm Female
PA2925D	Precision Adapter, 2.92mm Female To 3.5mm Male
PA2925F	Precision Adapter, 2.92mm Female To 3.5mm Female 4 Hole Flange
PA2525EB	PRECISION ADAPTER, 3.5MM FEMALE BULKHEADTO 3.5MM FEMALE
PA2525EA	Precision Adapter, 3.5mm Female Bulkhead to 3.5mm Female
ANO 291-941-1484-1	Adapter, 2.92mm Male To SMPM-T Male, Full Detent
ANO 291-941-1484-2	Adapter, 2.92mm Male To SMPM-T Male, Smooth Bore
ANO 292-932-2521	Adapter, Right Angle 2.92mm Female To SMP Female
ANO 292-941-1523-1	Adapter, 2.92mm Female To SMPM-T Male, Full Detent
ANO 292-941-1523-2	Adapter, 2.92mm Female To SMPM-T Male, Smooth Bore
ANO 931-931-1382-1	Adapter, SMP Straight Male Bulkhead To SMP Male, Full Detent
ANO 931-931-1382-2	Adapter, SMP Straight Male Bulkhead To SMP Male, Limited Detent
ANO 931-931-1382-3	Adapter, SMP Straight Male Bulkhead To SMP Male, Smooth Bore
ANO 931-931-1589-1	Adapter, SMP Straight Full Detent Male Bulkhead to SMP Full Detent Male
ANO 931-931-1589-2	Adapter, SMP Straight Limited Detent Male Bulkhead to SMP Limited Detent Male
ANO 931-931-1589-3	Adapter, SMP Straight Smooth Bore Male Bulkhead to SMP Smooth Bore Male
ANO 931-931-1589-4	Adapter, SMP Straight Limited Detent Male Bulkhead to SMP Full Detent Male
ANO 931-931-1589-5	Adapter, SMP Straight Full Detent Male Bulkhead to SMP Limited Detent Male
ANO 931-932-1559	Adapter, Right Angle SMP Male (FD)to SMP Female
ANO 932-932-1082	Adapter, SMP Female To SMP Female, L=6.45 [.254]
ANO 932-932-1252	Adapter, SMP Female To SMP Female, L=8.49 [.334]
ANO 932-932-1259	Adapter, SMP Female to SMP Female, L=6.17 [.243]
ANO 932-932-1260	Adapter, SMP Female To SMP Female, L=7.26 [.286]
ANO 932-932-1261	Adapter, SMP Female To SMP Female, L=10.03 [.395]
ANO 932-932-1264	Adapter, SMP Female to SMP Female, L=5.69 [.224]
ANO 932-932-1269	Adapter, SMP Female To SMP Female, L=14.28 [.562]



ANO 932-932-1271	Adapter, SMP Female To SMP Female, L=9.60 [.378]
ANO 932-932-1273	Adapter, SMP Female To SMP Female, L=9.40 [.370]
ANO 932-932-1274	Adapter, SMP Female To SMP Female, L=9.50 [.374]
ANO 932-932-1323	Adapter, SMP Female To SMP Female, L=22.40 [.882]
ANO 932-932-1407	Adapter, SMP Female To SMP Female, L=15.24 [.600]
ANO 932-932-1414	Adapter, SMP Female To SMP Female, L=7.00 [.276]
ANO 932-932-1465	Adapter, SMP Female To SMP Female, L=12.59 [.496]
ANO 932-932-1568	Adapter, SMP Female to SMP Female, L=14.88 [.586]
PA2229A	Precision Adapter, 2.4mm Male To 2.92mm Male
PA2229B	Precision Adapter, 2.4mm Male To 2.92mm Female
PA2229C	Precision Adapter 2.4mm Female To 2.92mm Female
PA2229CA	Precision Adapter, 2.4mm Female To 2.92mm Female, VSWR: 1.20 MAX.
PA2229D	Precision Adapter, 2.4mm Female To 2.92mm Male
PA2229E	Precision Adapter 2.4mm Female To 2.92mm Female 4 Hole Flange
PA2229J	Precision Adapter, Right Angle 2.4mm Male to 2.92mm Male
PA2229K	Precision Adapter, Right Angle 2.4mm Male to 2.92mm Female
PA2229L	Precision Adapter, Right Angle 2.4mm Female to 2.92mm Female
PA2229M	Precision Adapter, Right Angle 2.4mm Female to 2.92mm Male
PA2291C	Precision Adapter, 2.4mm Female to SSMA Female
PA2291D	Precision Adapter, 2.4mm Female to SSMA Male
PA2293C	Precision Adapter, 2.4mm Female to SMP Female
PA2929A	Precision Adapter, 2.92mm Male To 2.92mm Male
PA2929B	Precision Adapter 2.92mm Male To 2.92mm Female
PA2929C	Precision Adapter 2.92mm Female To 2.92mm Female
PA2929EA	Precision Adapter, 2.92mm Female Bulkhead To 2.92mm Female
PA2929EB	Precision Adapter, 2.92mm Bulkhead Waterproof Female to 2.92mm Female
PA2929EC	Precision Adapter, 2.92mm Bulkhead Waterproof Female to 2.92mm Female
PA2929F	Precision Adapter 2.92mm Female To 2.92mm Female 4 Hole Flange
PA2929FB	Precision Adapter, 2.92mm Female to 2.92mm Female, 2 Hole Flange



PA2929FC	Precision Adapter, 2.92mm Female to 2.92mm Female, 2 Hole Flange
PA2929J	Precision Adapter Right Angle 2.92mm Male To 2.92mm Male
PA2929K	Precision Adapter Right Angle 2.92mm Male To 2.92mm Female
PA2929L	Precision Adapter Right Angle 2.92mm Female To 2.92mm Female
PA2929S	Precision Adapter, 2.92mm Male to 2.92mm Bulkhead Female
PA2991A	Precision Adapter, 2.92mm Male To SSMA Male
PA2991B	Precision Adapter, 2.92mm Male To SSMA Female
PA2991C	Precision Adapter, 2.92mm Female To SSMA Female
PA2991D	Precision Adapter, 2.92mm Female To SSMA Male
PA2993A	Precision Adapter, 2.92mm Male to SMP Male
PA2993B	Precision Adapter, 2.92mm Male to SMP Female
PA2993C	Precision Adapter, 2.92mm Female To SMP Female
PA2993D	Precision Adapter, 2.92mm Female To SMP Male, Limited Detent
PA2994A	Precision Adapter, 2.92mm Male To SMPM Male
PA2994B	Precision Adapter, 2.92mm Male To SMPM Female
PA2994C	Precision Adapter, 2.92mm Female To SMPM Female
PA2994D	Precision Adapter, 2.92mm Female To SMPM Male
PA6229A	Precision Adapter, 1.85mm Male To 2.92mm Male
PA6229B	Precision Adapter, 1.85mm Male To 2.92mm Female
PA6229C	Precision Adapter, 1.85mm Female To 2.92mm Female
PA6229D	Precision Adapter, 1.85mm Female To 2.92mm Male
PA6422C	Precision Adapter, NMD2.92mm Female to 2.4mm Female
PA6429C	Precision Adapter, NMD2.92mm Female to 2.92mm Female
PA6429CA	Precision Adapter, NMD2.92mm Female to 2.92mm Female
PA6829C	Precision Adapter, NMD2.4mm Female To 2.92mm Female
PA6829CA	Precision Adapter, NMD2.4mm Female to 2.92 Female
PA6829D	Precision Adapter, NMD 2.4mm Female to 2.92mm Male
PA6864D	Precision Adapter, NMD2.4mm Female to NMD2.92mm Male
PA6929C	Precision Adapter, NMD1.85mm Female to 2.92mm Female



PA6929CA	Precision Adapter, NMD1.85mm Female to 2.92mm Female
PA6964D	Precision Adapter, NMD1.85mm Female to NMD2.92mm Male
PA9191A	Precision Adapter, SSMA Male to SSMA Male
PA9191B	Precision Adapter, SSMA Female to SSMA Male
PA9191C	Precision Adapter, SSMA Female to SSMA Female
PA2222B	Precision Adapter 2.4mm Male To 2.4mm Female
PA2222E	Precision Adapter 2.4mm Female Bulkhead To 2.4mm Female
PA6222A	Precision Adapter 1.85mm Male To 2.4 Mm Male
PA6222B	Precision Adapter 1.85mm Male To 2.4mm Female
PA6222C	Precision Adapter 1.85mm Female To 2.4mm Female
PA6222D	Precision Adapter 1.85mm Female To 2.4mm Male
PA6922C	Precision Adapter, NMD1.85mm Female to 2.4mm Female
PA6968D	Precision Adapter, NMD1.85mm Female to NMD2.4mm Male
PA6822C	Precision Adapter, NMD2.4mm Female to 2.4mm Female
PA6868B	Precision Adapter, NMD2.4mm Female to NMD2.4mm Male
PA2222C	Precision Adapter, 2.4mm Female to 2.4mm Female
PA2222BA	Precision Adapter, 2.4mm Male to 2.4mm Female
PA2222J	Precision Adapter, Right Angle 2.4mm Male to 2.4mm Male
PA2222K	Precision Adapter, Right Angle 2.4mm Male To 2.4mm Female
PA2222L	Precision Adapter, Right Angle 2.4mm Female to 2.4mm Female
PA6822D	Precision Adapter, NMD2.4mm Female to 2.4mm Male
PA6822B	Precision Adapter, NMD2.4mm Male to 2.4mm Female
PA2222F	Precision Adapter, 2.4mm Female to 2.4mm Female, 2 Hole Flange
PA2222FA	Precision Adapter, 2.4mm Female to 2.4mm Female, 2 Hole Flange
PA6922CA	Precision Adapter, NMD1.85mm Female to 2.4mm Female
PA6822CA	Precision Adapter, NMD2.4mm Female to 2.4mm Female
PA6222K	Precision Adapter, Right Angle 1.85mm Male to 2.4mm Female
PA6222L	Precision Adapter, Right Angle 1.85mm Female to 2.4mm Female
PA6222M	Precision Adapter, Right Angle 1.85mm Female to 2.4mm Male



PA6222J	Precision Adapter, Right Angle 1.85mm Male to 2.4mm Male
ANO 621-941-1524-1	Adapter, 1.85mm Male To SMPM-T Male, Full Detent
ANO 621-941-1524-2	Adapter, 1.85mm Male To SMPM-T Male, Smooth Bore
ANO 622-941-1525-1	Adapter, 1.85mm Female To SMPM-T Male Full Detent
ANO 622-941-1525-2	Adapter, 1.85mm Female To SMPM-T Male Smooth Bore
ANO 941-941-1456-1	Adapter, SMPM Male to SMPM Male, Full Detent
ANO 941-941-1456-2	Adapter, SMPM Male to SMPM Male, Smooth Bore
ANO 941-941-1512	Adatper, SMPM Male to SMPM Male
ANO 941-941-1542-1	Adapter, SMPM-T Male to SMPM-T Male, Full Detent
ANO 941-941-1542-2	Adapter, SMPM-T Male to SMPM-T Male, Smooth Bore
ANO 941-941-1546	Adapter, SMPM Male(FD) to SMPM Male(FD), Hermetic Seal
ANO 942-942-1381	Adapter, SMPM Female To SMPM Female, L=6.73 [.265]
ANO 942-942-1415	Adapter, SMPM Spring Loaded Female To SMPM Female
ANO 942-942-1526	Adapter, SMPM Female To SMPM Female, L=5.36 [.211]
ANO 942-942-1527	Adapter, SMPM Female To SMPM Female, L=12.7 [.500]
PA6262A	Precision Adapter, 1.85mm Male To 1.85mm Male
PA6262B	Precision Adapter 1.85mm Male To 1.85mm Female
PA6262C	Precision Adapter 1.85mm Female To 1.85mm Female
PA6262CA	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262E	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262EA	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262F	Precision Adapter, 1.85 Female to 1.85 Female 4 Hole Flange
PA6262FA	Precision Adapter, 1.85mm Female to 1.85mm Female, 2 Hole Flange
PA6262FB	Precision Adapter, 1.85mm Female to 1.85mm Female, 4 Hole Flange
PA6262J	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Male
PA6262K	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Female
PA6262L	Precision Adapter, Right Angle 1.85mm Female To 1.85mm Female
PA6262S	Precision Adapter, 1.85mm Bulkhead Male to 1.85mm Female
PA6276A	Precision Adapter, 1.0mm Male to 1.85mm Male



PA6276B	Precision Adapter, 1.0mm Male to 1.85mm Female
PA6276C	Precision Adapter, 1.0mm Female to 1.85mm Female
PA6276D	Precision Adapter, 1.0mm Female to 1.85mm Male
PA6278A	Precision Adapter, SMPS Male Full Detent to 1.85mm Male
PA6278D	Precision Adapter, SMPS Male Full Detent To 1.85mm Female
PA6294A	Precision Adapter, 1.85mm Male To SMPM Male
PA6294B	Adapter, 1.85mm Male to SMPM Female
PA6294C	Adapter, 1.85mm Female to SMPM Female
PA6294D	Precision Adapter, 1.85mm Female To SMPM Male
PA6962B	Precision Adapter, NMD1.85mm Male to 1.85mm Female
PA6962C	Precision Adapter, NMD1.85mm Female to 1.85mm Female
PA6962CA	Precision Adapter, NMD1.85mm Female To 1.85mm Female
PA6962D	Precision Adapter, NMD1.85mm Female to 1.85mm Male
PA6962S	Precision Adapter, NMD1.85mm Male To 1.85mm Female,Panel Mount
PA6969B	Precision Adapter, NMD1.85mm Female to NMD1.85mm Male
PA7678D	Precision Adapter, SMPS Male Full Detent to 1.0mm Female
PA8062A	Precision Adapter, 1.35mm Male To 1.85mm Male
PA8062B	Precision Adapter, 1.35mm Female to 1.85mm Male
PA8062C	Precision Adapter, 1.35mm Female To 1.85mm Female
PA8062D	Precision Adapter, 1.35mm Male to 1.85mm Female
PA8080C	Precision Adapter, 1.35mm Female To 1.35mm Female
PA8080B	Precision Adapter, 1.35mm Male To 1.35mm Female
PA8080A	Precision Adapter, 1.35mm Male To 1.35mm Male
PA7680C	Precision Adapter, 1.0mm Female To 1.35mm Female
PA7680A	Precision Adapter, 1.0mm Male To 1.35mm Male
PA7680B	Precision Adapter, 1.0mm Male to 1.35mm Female
PA7680D	Precision Adapter, 1.0mm Female to 1.35mm Male
PA7676A	Precision Adapter, 1.0mm Male to 1.0mm Male
PA7676C	Precision Adapter, 1.0mm Female to 1.0mm Female

PA7676B	Precision Adapter, 1.0mm Female to 1.0mm Male
PA7676F	Precision Adapter, 1.0mm Female to 1.0mm Female 4 Hole .375" Flange
PA7676Q	Precision Adapter, 1.0mm Male to 1.0mm Male, Flange Mount
PA7676BA	Adapter, Panel Mount, Ruggedized 1.0mm Male to 1.0mm Female
PA7676CA	Ruggedized 1.0mm Adapter, Female to Female
PA7676AA	Adapter, Panel Mount, Ruggedized 1.0mm Male to 1.0mm Male

CABLES

Product Name	Description
AFLEX-141	AFLEX Series Cable, AFLEX-141 with FEP Jacket
AFLEX-047	AFLEX Series Cable, AFLEX-047 with Blue FEP Jacket
AFLEX-086AF	AFLEX Series Cable, AFLEX-086AF with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
AFLEX-141AF	AFLEX Series Cable, AFLEX-141AF with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
EP135	EP Series Cable, EP135 with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
PLEX140-lite	PLEX-lite Series Cable, PLEX140-lite with eTFE Jacket
PLEX150P	PLEX Series Cable, PLEX150P With Gray FEP Jacket
SR120-LL-AP	Semi-Rigid Series Cable, ANO SR120 -LL-AP with Alloy Plated Seamless Copper Tube
SR141TP-LL	Low Loss Semi-Rigid Series Cable, SR141TP-LL
SUPO-120	SUPO Series Cable, SUPO-120 with FEP Jacket
SUPO-150	SUPO Series Cable, SUPO-150 with FEP Jacket
SUPO-150G	SUPO Series Cable, SUPO-150G with Silicone Rubber Jacket
SUPO-155B	SUPO Series Cable, SUPO-155B with FEP Jacket
PLEX140	PLEX Series Cable, PLEX140 With FEP Jacket
PLEX140VT	PLEX Series Cable, PLEX140VT With Violet (PANTONE 2583C) FEP Jacket
EP180	EP Series Cable, EP180 with TPU Jacket
MB103	MB Series Cable, MB103 With Blue FEP Jacket
PLEX130P	PLEX Series Cable, PLEX130P With Blue FEP Jacket
PLEX135	PLEX Series Cable, PLEX135 With Gray FEP Jacket
SUPO-125	SUPO Series Cable, SUPO-125 with FEP Jacket
ANO HF086FEP(BK)	Hand-Formable Series Cable, HF086FEP(BK) with Black FEP Jacket



RG405	RG Series Semi-rigid Cable, 50 Ohm, With Copper Tube
SR086	Semi-Rigid Series Cable, 50 Ohm, with Copper Tube
AFLEX-086	AFLEX Series Cable, AFLEX-086 with FEP Jacket
SR086LL	Low Loss Semi-Rigid Series Cable, 50 Ohm, With Copper Tube
SR086TP-LL	Low Loss Semi-Rigid Series Cable, SR086TP-LL
HTC-047P	Flexible Coaxial Cable, HTC-047P with Blue FEP Jacket
MB098	MB Series Cable, MB098 With Blue FEP Jacket
PLEX090	PLEX Series Cable, PLEX090 With FEP Jacket
PLEX090-lite	PLEX-lite Series Cable, PLEX090-lite with eTFE Jacket
PLEX090DBK	PLEX Series Cable, PLEX090DBK With Black FEP Jacket
PLEX102P	PLEX Series Cable PLEX102P With FEP Jacket
PLEX102S	PLEX Series Cable, PLEX102S With Blue PUR Jacket
SR070LL-TP	Low Loss Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube
SUPO-057P	SUPO Series Cable, SUPO-057P with FEP Jacket
SUPO-059	SUPO Series Cable, SUPO-059 with FEP Jacket
SUPO-090	SUPO Series Cable, SUPO-090 with FEP Jacket
SR047	Semi-Rigid Series Cable, 50 Ohm, with Copper Tube
SR047TP	Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube
SR047TP-LL	Low Loss Semi-Rigid Series Cable, 50 Ohm, SR047TP-LL with Tin Plated Copper Tube, 110 GHz
SUPO-059P	SUPO Series Cable, SUPO-059P with FEP Jacket
SR034	Semi-Rigid Series Cable, 50 Ohm, with Copper Tube
SR034PFA	Semi-Rigid Series Cable, 50 Ohm, SR034PFA with Copper Tube
SR031LL	Low Loss Semi-Rigid Series Cable, 50 Ohm, with Copper Tube

CABLE ASSEMBLIES

Product Name	Description
AF086-NRP-SMPMM-12	Cable Assembly, NanoRF Pin to SMPM Male Smooth Bore Interface Fit M38999 Size 12 Insert, ANO AFLEX-086 Cable, 12 Inches
AF086-SMPMF-SMPMF-12	Cable Assembly, M38999 Size 12 Insert SMPM Female to M38999 Size 12 Insert SMPM Female, ANO AFLEX-086 Cable, 12 Inches
AF086-SMPMF-SMPMM-12	Cable Assembly, VITA67.3 Plug-in Contact SMPM Female to SMPM Male Smooth Bore Interface Fit M38999 Size 12 Insert, ANO AFLEX-086 Cable, 12 Inches
P090D-29M-SMPMTF-36	Cable Assembly, 2.92mm Straight Male to SMPM-T Straight Female, PLEX-090D, 36 Inches

PT-29F-29F-26	Cable Assembly, 2.92mm Female to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29F-29F-39	Cable Assembly, 2.92mm Female to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-18F-26	Cable Assembly, 2.92mm Male to 1.85mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-18F-39	Cable Assembly, 2.92mm Male to 1.85mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-24F-26	Cable Assembly, 2.92mm Male to 2.4mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-24F-39	Cable Assembly, 2.92mm Male to 2.4mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-29F-26	Cable Assembly, 2.92mm Male to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-29F-39	Cable Assembly, 2.92mm Male to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-29M-26	Cable Assembly, 2.92mm Male to 2.92mm Male, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-29M-39	Cable Assembly, 2.92mm Male to 2.92mm Male, PT-29 (PT Series Precision Test Cables), 39 Inches
SR086LL-29M-29F-77MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Female, SR086LL Cable, 0.077 Meters
SR086LL-29M-29M-81MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Male, SR086LL Cable, 0.081 Meters
SR120LL-29M-29F-318MM	Cable Assembly, 2.92mm Straight Male to 2.92 Straight Female, SR120LL Cable, 0.318 Meters
SR120LL-29M-29M-215MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Female, SR120LL Cable, 0.215 Meters
VN-NMD18F-29F-26	Cable Assembly, NMD1.85mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD18F-29F-39	Cable Assembly, NMD1.85mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches
VN-NMD18F-29M-26	Cable Assembly, NMD1.85mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD18F-29M-39	Cable Assembly, NMD1.85mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches
VN-NMD24F-29F-26	Cable Assembly, NMD2.4mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD24F-29F-39	Cable Assembly, NMD2.4mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches
VN-NMD24F-29M-26	Cable Assembly, NMD2.4mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD24F-29M-39	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches
VN-NMD29F-29F-26	Cable Assembly, NMD2.92mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD29F-29F-39	Cable Assembly, NMD2.92mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches
VN-NMD29F-29M-26	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD29F-29M-39	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches
PT-24F-18M-26	Cable Assembly, 2.4mm Female to 1.85mm Male, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24F-18M-39	Cable Assembly, 2.4mm Female to 1.85mm Male, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24F-24F-26	Cable Assembly, 2.4mm Female to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 26 Inches



PT-24F-24F-39	Cable Assembly, 2.4mm Female to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24M-24F-26	Cable Assembly, 2.4mm Male to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24M-24F-39	Cable Assembly, 2.4mm Male to 2.4mm Female, PT-24 (PT Series Precision Test Cables), 39 Inches
PT-24M-24M-26	Cable Assembly, 2.4mm Male to 2.4mm Male, PT-24 (PT Series Precision Test Cables), 26 Inches
PT-24M-24M-39	Cable Assembly, 2.4mm Male to 2.4mm Male, PT-24 (PT Series Precision Test Cables), 39 Inches
SR086TPLL-24F-24M-970MM	Cable Assembly, 2.4mm Straight Female to 2.4mm Straight Male, ANO SR086TP-LL Cable, 0.97 meters
VN-NMD18F-24F-26	Cable Assembly, NMD1.85mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 26 Inches
VN-NMD18F-24F-39	Cable Assembly, NMD1.85mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 39 Inches
VN-NMD18F-24M-26	Cable Assembly, NMD1.85mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 26 Inches
VN-NMD18F-24M-39	Cable Assembly, NMD1.85mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 39 Inches
VN-NMD24F-24F-26	Cable Assembly, NMD2.4mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 26 Inches
VN-NMD24F-24F-39	Cable Assembly, NMD2.4mm Female to 2.4mm Female, VN-24 (VNA Test Cable), 39 Inches
VN-NMD24F-24M-26	Cable Assembly, NMD2.4mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 26 Inches
VN-NMD24F-24M-39	Cable Assembly, NMD2.4mm Female to 2.4mm Male, VN-24 (VNA Test Cable), 39 Inches
047X-18F-18F-15	047X Coaxial Cable 1.85mm Female to 1.85 Female
PT-18F-18F-26	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18F-18F-39	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
PT-18M-18F-26	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18M-18F-39	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
PT-18M-18M-26	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18M-18M-39	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 39 Inches
VN-NMD18F-18F-26	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 26 Inches
VN-NMD18F-18F-39	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 39 Inches
VN-NMD18F-18M-26	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 26 Inches
VN-NMD18F-18M-39	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 39 Inches
AF047-13M-13M-300MM	AF047 Coaxial Cable, 1.35mm Male to 1.35mm Male
AF047-1M-1F-8	AFLEX-047 Coaxial Cable 1mm Male to 1mm Female, 8 Inches
AF047-1M-1M-100MM	047 Coaxial Cable 1mm Male to 1mm Male, 100mm
AF047-1M-1M-6	AFLEX-047 Coaxial Cable 1mm Male to 1mm Male, 6 Inches

[PT-1M-1F-16CM](#)

Precision Test Cable, 1mm Male to 1mm Female Connector, PT-10 (PT Series Precision Test Cables)

[PT-1M-1M-16CM](#)

Precision Test Cable, 1mm Male to 1mm Male Connector, PT-10 (PT Series Precision Test Cables)

TERMINATIONS

Product Name	Description
ANO 776-101	Coaxial Termination, 1 Watt, 1.0mm Male DC-110 GHz
ANO 725-106	Coaxial Termination With Chain 3.5mm Male, 1 Watt, DC-33 GHz
ANO 791-101	Coaxial Termination, SSMA Male, 1 Watt, DC-33 GHz
ANO 729-101	Coaxial Termination, 2.92mm Male, 2 Watts, DC-40GHz
ANO 729-103	Coaxial Termination With Chain 2.92mm Male, 2 Watt, DC-40GHz
ANO 729-106	Coaxial Termination, 2.92 Mm Male, 5 Watts, DC-40GHz
ANO 729-108	Coaxial Termination, 2.92 Mm Male, 10 Watts, DC-40GHz
ANO 729-110	Coaxial Termination, 2.92 mm Male, 15 Watts, DC-40GHz
ANO 729-112	Coaxial Termination, 2.92 mm Male, 20 Watts, DC-40GHz
ANO 729-114	Coaxial Termination, 2.92 mm Male, 25 Watts, DC-40GHz
ANO 729-116	Coaxial Termination, 2.92 mm Male, 30 Watts, DC-40GHz
ANO 729-118	Coaxial Termination, 2.92mm Male, 40 Watts, DC-40GHz
ANO 729-119	Coaxial Termination, 2.92mm Male, 50 Watts, DC-40GHz
ANO 729-120	Coaxial Termination, 2.92mm Male, 60 Watts, DC-40GHz
ANO 729-123	Coaxial Termination With Chain 2.92mm Male, 2 Watt, DC-40GHz
ANO 729-202	Coaxial Termination, 2.92mm Female, 2 Watts, DC-40GHz
ANO 729-207	Coaxial Termination, 2.92 mm Female, 5 Watts, DC-40GHz
ANO 729-209	Coaxial Termination, 2.92 mm Female, 10 Watts, DC-40GHz
ANO 729-211	Coaxial Termination, 2.92 mm Female, 15 Watts, DC-40GHz
ANO 729-213	Coaxial Termination, 2.92 mm Female, 20 Watts, DC-40GHz
ANO 729-215	Coaxial Termination, 2.92 mm Female, 25 Watts, DC-40GHz
ANO 729-217	Coaxial Termination, 2.92 mm Female, 30 Watts, DC-40GHz
ANO 794-104	Coaxial Termination, SMPM Male, 0.25 Watts, DC~40GHz
ANO 794-107-1	Coaxial Termination, SMPM Male, Full Detent, 0.5 Watts, DC-40 GHz
ANO 794-107-2	Coaxial Termination, SMPM Male, Smooth Bore, 0.5 Watts, DC-40 GHz



ANO 794-203	Coaxial Termination, SMPM Female, 0.25 Watts, DC~40GHz
ANO 722-103	Coaxial Termination 2.4mm Male, 1.0 Watts, DC~50GHz
ANO 722-105	Coaxial Termination With Chain, 2.4mm Male, 1.0 Watts, DC-50GHz
ANO 722-204	Coaxial Termination 2.4mm Female, 1.0 Watts, DC~50GHz
ANO 722A-1.20	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 1.20
ANO 722A-1.50	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 1.50
ANO 722A-2.00	Precision Standard Mismatches Coaxial Termination, 2.4mm Male, 2 Watts, DC-50GHz, Nominal VSWR 2.00
ANO 722B-1.20	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 1.20
ANO 722B-1.50	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 1.50
ANO 722B-2.00	Precision Standard Mismatches Coaxial Termination, 2.4mm Female, 2 Watts, DC-50GHz, Nominal VSWR 2.00
ANO 762-101	Coaxial Termination, 1Watt, 1.85mm Male DC-67GHz, VSWR 1.35 Max.
ANO 762-108	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67GHz, VSWR 1.30 Max.
ANO 762-111	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.
ANO 762-202	Coaxial Termination, 1 Watt, 1.85mm Female DC-67GHz, VSWR 1.35 Max.
ANO 762-212	Coaxial Termination, 1.85mm Female, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.
ANO 784-102	Coaxial Termination, SMPS Male, 0.25 Watts, DC-70GHz
ANO 784-201	Coaxial Termination, SMPS Female, 0.25 Watts, DC-70GHz

ATTENUATORS

Product Name	Description
ANO 25-5001-06	6 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz
ANO 25-5001-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz
ANO 25-5001-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz
ANO 25-5001-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz
ANO 25-5001-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female, 50 Watts, DC-30 GHz
ANO 25-10001-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz
ANO 25-10001-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz
ANO 25-10001-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz
ANO 25-10001-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female, 100 Watt, DC-31 GHz
ANO 25-1001-01	1 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz

ANO 25-1001-02	2 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-03	3 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-04	4 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-05	5 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-06	6 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-07	7 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-08	8 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-09	9 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-15	15 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-25	25 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 25-1001-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female, 10 Watts, DC-32 GHz
ANO 29-0209-01	1dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-02	2 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-03	3 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-04	4 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-05	5 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-06	6 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-07	7 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-08	8 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-09	9 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 29-0209-40	40 dB Attenuator, 2.92mm Male to 2.92 Female, 2 Watts, DC-32 GHz
ANO 25-0201-31	31 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz



ANO 25-0201-32	32 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-33	33 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-34	34 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-36	36 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-37	37 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-38	38 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-39	39 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0201-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-01	1 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-02	2 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-03	3 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-04	4 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-05	5 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-06	6 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-07	7 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-08	8 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-09	9 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-10	10 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-15	15 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-20	20 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-25	25 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-30	30 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-35	35 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 25-0202-40	40 dB Attenuator, 3.5mm Male to 3.5mm Female 2 Watt, DC-34 GHz
ANO 29-0202-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz



ANO 29-0202-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0203-01	1 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-02	2 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-03	3 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-04	4 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-05	5 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-06	6 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-07	7 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-08	8 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-09	9 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-10	10 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-15	15 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-20	20 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-25	25 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-30	30 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0206-01	1 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-02	2 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-03	3 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-04	4 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-05	5 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz



ANO 29-0206-06	6 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-07	7 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-08	8 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-09	9 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-10	10 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-15	15 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-20	20 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-25	25 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-30	30 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-31	31 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-32	32 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-33	33 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-34	34 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-35	35 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-36	36 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-37	37 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-38	38 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-39	39 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-40	40 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0501-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz



ANO 29-0501-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0502-01	1 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-02	2 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-03	3 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-04	4 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-05	5 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-06	6 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-07	7 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-08	8 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-09	9 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-15	15 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-25	25 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-1001-01	1dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-02	2dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-03	3dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-04	4dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-05	5dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-06	6dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-07	7dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-08	8dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-09	9dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-10	10dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-15	15dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional



ANO 29-1001-20	20dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-25	25dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-30	30dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1502-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-40	40 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1504-03	3 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-04	4 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-05	5 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-06	6 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-07	7 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-08	8 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-09	9 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-10	10 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-20	20 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-30	30 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-40	40 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-2001-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz



ANO 29-2001-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2002-10	10 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-10	10 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2501-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-50	50 dB Attenuator, 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-3001-10	10 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-20	20 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-4001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 40 Watt, DC-40GHz
ANO 29-4001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 40 Watt, DC-40GHz
ANO 29-5001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5002-50	50dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5002-60	60 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5003-30	30dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5003-40	40dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-6001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 60 Watt, DC-40GHz
ANO 29-6001-40	40dB Attenuator, 2.92mm Male To 2.92mm Female 60 Watt, DC-40GHz

ANO 29-0207-01	1 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-02	2 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-03	3 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-04	4 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-05	5 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-06	6 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-07	7 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-08	8 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-09	9 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-10	10 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-15	15 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-20	20 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-25	25 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-30	30 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0504-01	1dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-02	2dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-03	3dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-04	4dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-05	5dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-06	6dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-07	7dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-08	8dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-09	9dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-10	10dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-15	15dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-20	20dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-25	25dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-35	35dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-40	40dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz



ANO 22-0203-01	1dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-02	2dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-03	3dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-04	4dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-05	5dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-06	6dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-07	7dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-08	8dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-09	9dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-10	10dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-20	20dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-25	25dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0203-30	30dB Attenuator, 2.4mm Male To 2.4mm Female, 2w, DC-50GHz
ANO 22-0205-01	1 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-02	2 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-03	3 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-04	4 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-05	5 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-06	6 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-07	7 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-08	8 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-09	9 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-10	10 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-15	15 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-20	20 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-25	25 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0205-30	30 dB Attenuator, 2.4mm Male to 2.4mm Female, 2W, DC-50GHz
ANO 22-0501-01	1 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-02	2 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz



ANO 22-0501-03	3 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-04	4 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-05	5 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-06	6 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-07	7 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-08	8 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-09	9 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-10	10 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-15	15 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-20	20 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-25	25 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-30	30 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-0501-40	40 dB Attenuator, 2.4mm Male to 2.4mm Female, 5 Watts, DC-50 GHz
ANO 22-1001-03	3 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-04	4 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-05	5 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-06	6 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-07	7 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-08	8 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-09	9 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-10	10 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-15	15 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-20	20 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-30	30 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1001-40	40 dB Attenuator, 2.4mm Male to 2.4mm Female, 10 Watts, DC-50 GHz
ANO 22-1501-03	3 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-04	4 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-05	5 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-06	6 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz



ANO 22-1501-07	7 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-08	8 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-09	9 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-10	10 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-20	20 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-30	30 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 22-1501-40	40 dB Attenuator, 2.4mm Male to 2.4mm Female, 15 Watts, DC-50 GHz
ANO 62-0201-01	1dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-02	2dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-03	3dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-04	4dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-05	5dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-06	6dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-07	7dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-08	8dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-09	9dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-10	10dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-15	15dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-20	20dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-25	25dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-30	30dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-40	40dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0501-01	1 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-02	2 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-03	3 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-04	4 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-05	5 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-06	6 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-07	7 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz

ANO 62-0501-08	8 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-09	9 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-10	10 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-15	15 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-20	20 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-25	25 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-30	30 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-40	40 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz

POWER DIVIDER

Product Name	Description
PD2902A	1-40GHz 2-Way 2.92 Power Divider
PD2902	27-29 GHz 2-Way 2.92mm Power Divider

DC BLOCKS

Product Name	Description
D29-A1	Inner DC Block From 30 MHz To 40 GHz With 2.92mm Connector
D22-A1	Inner DC Block From 30 MHz TO 50 GHz With 2.4mm Connector
D62-A1	DC Block on Inner Conductor 1.85mm Male to 1.85mm Female Operating From 50 MHz to 67 GHz

TOOLS

Product Name	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque=8±0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12±0.48 in.lbs, Hex Size =5/16 in.
ANO TW-019	Torque Wrench for SMA Type Connectors, Preset Torque= 5±0.2 in.lbs, Hex Size =5/16 in.
ANO TWSD-001	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9±0.04 NM [8±0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue
T29002-1	Fixed Wrench for Bulkhead 2.92mm/SMA Connectors (Hex 11mm)

ACCESSORIES

Product Name	Description
ANO 2211-6055	Cap Male, With Chain for 2.4mm and 1.85mm
ANO 2111-6099	Cap, Male With Chain for SMA, 3.5mm, 2.92mm



[ANO 2211-6055](#)

Cap Male, With Chain for 2.4mm and 1.85mm