

18 GHz Products



CONNECTORS

Part Number	Description
ANO 1411-2007	BMA Straight Plug Crimp For LMR100/ RG316/ RG174 Cable
ANO 1411-3003	BMA Straight Plug Slide-On Connector Solder Attachment, 2 Hole Flange Mount Stub Terminal .481" Hole Spacing, Tab Contact
ANO 1411-3012	BMA Straight Plug Slide-On Connector Solder Attachment, 2 Hole Flange Mount Stub Terminal .481" Hole Spacing With Emi Gasket
ANO 1411-5010	BMA Straight Jack Thread-in Hermetic
ANO 1412-3006	BMA Straight Jack Slide-On Solder Attachment 2 Hole Flange Mount Stub Terminal .481" Hole Spacing, With Cylindrical Contact
ANO 1412-5011	BMA Straight Plug Thread-in Hermetic
ANO 2111-2058	SMA Straight Male Solder For RG402/ SMT680-141/ 670-141 Cable
ANO 2111-2228	SMA STRAIGHT MALE PCB MOUNT RECEPTACLE
ANO 2111-2379	SMA STRAIGHT MALE SOLDER FOR .141 CABLE
ANO 2111-2381	SMA Straight Male Solder For PLEX-210 Cable
ANO 2111-2475	SMA Push on Straight Male Solder for AFLEX-086 Cable
ANO 2111-2537	SMA Straight Male Solder For .086 Cable With Loose Coupling Nut
ANO 2111-2540	SMA Straight Male Solder for IW2801, PLEX-310 Cable
ANO 2111-2554	SMA Straight Male Solder For IW2803 Cable
ANO 2111-4593	SMA End Launch Male for .062 PCB Receptacle-Tab Contact
ANO 2112-1022	SMA Straight Bulkhead Female Solder for .086 Cable, Body: Gold Plated Brass
ANO 2112-1022-1	SMA Straight Bulkhead Female Solder for .086 Cable, Body: Gold Plated Stainless Steel
ANO 2112-1057	SMA Straight Bulkhead Waterproof Female Solder For .086 Cable
ANO 2112-1059	SMA Straight Bulkhead Waterproof Female Solder For .141 Cable
ANO 2112-1062	SMA Straight Female, Bulkhead Waterproof, Solder For 047SC-2901 Cable
ANO 2112-1550	SMA Straight Bulkhead Waterproof Female Solder For .086 Cable
ANO 2112-2044	SMA Straight Female 2 Hole Flange, .480" Hole Spacing, For .086 Cable
ANO 2112-2269	SMA Straight Female Soler For .086 Cable
ANO 2112-2365	SMA Straight Female 2 Hole Flange, .480" Hole Spacing, For .086 Cable
ANO 2112-2438	SMA Straight Female, Solder For SR141 Cable
ANO 2112-2451	SMA Straight Female, Solder For SR141 Cable
ANO 2112-3024	SMA Straight Female, 4 Hole .500" SQ. Flange Mount Accept .018" Dia. Pin

18 GHz Products



ANO 2112-3031	SMA Straight Female, 2 Hole Flange Mount Accept .018" Pin, .480" Hole Spacing
ANO 2112-3036	SMA Straight Female, 2 Hole Flange, .480" Hole Spacing, Mount Receptacle, Body: Gold Plated Brass
ANO 2112-3036-1	SMA Straight Female, 2 Hole Flange, .480" Hole Spacing, Mount Receptacle, Body: Passivated Stainless Steel
ANO 2112-3036-2	SMA Straight Female, 2 Hole Flange, .480" Hole Spacing, Mount Receptacle, Body: Albaloy Plated Brass
ANO 2112-3070	SMA Straight Female, 4 Hole .500" SQ. Flange Mount, Body: Passivated Stainless Steel, Center Contact: Gold Plated Beryllium Copper Alloy
ANO 2112-3070-1	SMA Straight Female, 4 Hole .500" SQ. Flange Mount, Body: Gold Plated Brass, Center Contact: Gold Plated Beryllium Copper Alloy
ANO 2112-3070-2	SMA Straight Female, 4 Hole .500" SQ. Flange Mount, Body: Albaloy Plated Brass, Center Contact: Silver Plated Beryllium Copper Alloy
ANO 2112-3070-3	SMA Straight Female, 4 Hole .500" SQ. Flange Mount, Body: Gold Plated Stainless Steel, Center Contact: Gold Plated Beryllium Copper Alloy
ANO 2112-3091	SMA Straight Female 4 Hole Flange Solder For .141 Cable
ANO 2112-3134	SMA 4 Hole Flange Mount Female Receptacle
ANO 2112-3204	SMA Straight Female, 2 Hole Flange, .481" Hole Spacing, Receptacle With Solder Pot Contact
ANO 2112-3205	SMA Straight Female, 4 Hole .500" SQ. Flange Receptacle With Solder Post Contact, Body: Gold Plated Brass
ANO 2112-3205-1	SMA Straight Female, 4 Hole .500" SQ. Flange Receptacle With Solder Post Contact, Body: Passivated Stainless Steel
ANO 2112-3265	SMA Straight Female, 2 Hole Flange, .480" Hole Spacing, Solder For SR047 Cable With Captive Contact
ANO 2112-3301	SMA Straight Female, 2 Hole Flange Mount Receptacle, Extended Post And Ins., .480" Hole Spacing
ANO 2112-3318	SMA Female, 4 Hole, .500" SQ. Flange Mount, Post Contact, Body: Gold Plated Stainless Steel
ANO 2112-3318-1	SMA Female, 4 Hole, .500" SQ. Flange Mount, Post Contact, Body: Passivated Plated Stainless Steel
ANO 2112-3320	SMA Straight Female, 1/2 Inch Square, 4 Hole Flange Mount With Cylindrical Contact
ANO 2112-3364	SMA Female, 4 Hole .500" SQ. Flange Mount, Tab Contact
ANO 2112-3385	SMA Straight Female Solder Attachment 4 Hole .689" SQ. Flange Stub Terminal
ANO 2112-3397	SMA Straight Female, 4 Hole .500" SQ. Flange Solder For .086 Cable, Body: Gold Plated Brass
ANO 2112-3397-1	SMA Straight Female, 4 Hole .500" SQ. Flange Solder For .086 Cable, Body: Gold Plated Stainless Steel
ANO 2112-3400	SMA Straight Female, 2 Hole Flange, .481" Hole Spacing, Solder For SR047 Cable With Captive Contact
ANO 2112-3407	SMA Straight Female, 4 Hole .500" SQ. Flange Receptacle, Tab Contact
ANO 2112-3410	SMA Straight Female Connector Solder Attachment 2 Hole Flange, .481" Hole Spacing, Mount Stub Terminal, Body: Gold Plated Brass
ANO 2112-3410-1	SMA Straight Female Connector Solder Attachment 2 Hole Flange, .481" Hole Spacing, Mount Stub Terminal, Body: Nickel Plated Brass
ANO 2112-3414	SMA Straight Female 2 Hole Flange .500" Long, Accept .020" Pin Dia, Field Replaceable
ANO 2112-3444	SMA Straight Female, 4 Hole Flange Mount Post Contact
ANO 2112-3446	SMA Straight Female 2 Hole Flange, .374" Hole Spacing, Extended Post

18 GHz Products



ANO 2112-3452	SMA Straight Bulkhead Female 4 Hole Flange Receptacle
ANO 2112-3493	SMA Straight Female, 4 Hole .375" SQ. Flange Mount
ANO 2112-3517	SMA Female, 4 Hole Flange Mount, Tab Contact
ANO 2112-3519	SMA Female, 4 Hole .500" SQ. Flange Mount, Post Contact
ANO 2112-3526	SMA Straight Female, 4 Hole .375 SQ. Flange Mount Solder Cup Contact
ANO 2112-3547	SMA Straight Female, Solder Attachment 4 Hole .500 SQ. Flange Mount Stub Terminal, .340 Inch Hole Spacing Mechanically Captivated Contact
ANO 2112-3576	SMA Female, 2 Hole Flange Mount, .05 Pin Extended Dielectric, Post Contact
ANO 2112-3602	SMA Straight Female, 4 Hole .375 SQ. Flange Mount
ANO 2112-3607	SMA Female, 4 Hole Flange Mount, 0.64 Contact, Body: Passivated Stainless Steel
ANO 2112-4016	SMA Straight Female Edge Mount for .069 Board Thickness PCB
ANO 2112-4019	SMA Straight Bulkhead Female For PCB Mount
ANO 2112-4065	SMA Straight Female End Launch Receptacle Board Thickness 1.57 [.062]
ANO 2112-4084	SMA Straight Female Edge Mount For .037 Board Thickness PCB
ANO 2112-4130	SMA Straight Female Solder Attachment Thru Hole PCB, .200 Inch X .067 Inch Hole Spacing
ANO 2112-4143-1	SMA Straight Bulkhead Waterproof Female For PCB, Body: Gold Plated Brass
ANO 2112-4143-2	SMA Straight Bulkhead Waterproof Female For PCB, Body: Nickel Plated Brass
ANO 2112-4303	SMA End Launch Jack Receptacle- Tab Contact, Board Thickness= 1.07 [.042]
ANO 2112-4304	SMA End Launch Jack Receptacle-Tab Contact, Board Thickness= 1.57 [.062]
ANO 2112-4371	SMA End Launch Female For .062 PCB Receptacle,àTab Contact
ANO 2112-4389	SMA Straight End Launch Female For PCB Receptacle-Tab Contact
ANO 2112-4428	SMA Straight Female 2 Hole Flange .500" Long, Extended Post
ANO 2112-4534	SMA Female End Launch, PCB Mount, 15 Mil Pin
ANO 2112-4559	SMA Female Strip Transmission Line 2 Hole Launch With Round Contact
ANO 2112-4578	SMA Female Right Angle End Launch
ANO 2112-4579-00	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=0.60 [.024]
ANO 2112-4579-01	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=0.80 [.031]
ANO 2112-4579-02	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.00 [.039]
ANO 2112-4579-03	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.10 [.043]
ANO 2112-4579-04	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.20 [.047]

18 GHz Products



ANO 2112-4579-05	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.30 [.051]
ANO 2112-4579-06	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.50 [.059]
ANO 2112-4579-07	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.60 [.063]
ANO 2112-4579-08	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=1.73 [.068]
ANO 2112-4579-09	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=2.10 [.083]
ANO 2112-4579-10	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=2.25 [.089]
ANO 2112-4579-11	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=3.60 [.142]
ANO 2112-4579-12	SMA Straight Female Edge Mount Board Thickness PCB, Tab Thickness=3.80 [.150]
ANO 2112-4622	SMA Female Straight Bulkhead Waterproof, for PCB Mount
ANO 2112-5201	SMA Straight Female, Press Fit Receptacle Tab Contact
ANO 2112-5202	SMA Straight Female, Press Fit Receptacle Round Contact
ANO 2112-5203	SMA Straight Female, Press Fit Receptacle Round Contact
ANO 2112-5287	SMA Straight Female Pressmount Receptacle
ANO 2112-5455	SMA Female, Front Mounted Bulkhead with Slot Solder, .125 Thickness Panel
ANO 2112-5539	SMA Female Bulkhead Mount Hermetically Sealed Connector Solder Attachment Stub Terminal .250 inch Diameter, Front Mount IP67 Rated
ANO 2121-2378	SMA Right Angle Male Solder For .141 Cable, Captivated Contact
ANO 2121-2380	SMA R/A Male Solder For PLEX-210 Cable
ANO 2122-2329	SMA Right Angle Female Solder For .086 Cable Captivated Contact
ANO 2122-3071	SMA R/A Female, 4 Hole .500" SQ. Flange Mount Receptacle, Body: Passivated Stainless Steel
ANO 2122-3071-1	SMA R/A Female, 4 Hole .500" SQ. Flange Mount Receptacle, Body: Gold Plated Brass
ANO 2122-3468	SMA R/A Female, 4 Hole .50 Flange Mount Panel
ANO 2122-3474	SMA R/A Female, 4 Hole .500" SQ. Flange Mount Receptacle
ANO 2122-4158	SMA Straight Female PCB Receptacle, 4 Hole .500" SQ. Flange
ANO 2611-2001	QMA Straight Male Solder For .141 Cable, Captivated Contact
ANO 2611-2038	QMA Straight Male Solder For .047 Cable
ANO 2611-2101	QMA Straight Male Solder For .086 Cable
ANO 2611-2102	QMA Straight Male Solder For .141 Cable
ANO 2611-2111	QMA Straight Male Crimp for LMR240 Cable
ANO 2612-1012	QMA Straight Female Bulkhead Solder For .141 Cable captivated Contact

18 GHz Products



ANO 2612-1030	QMA Straight Female Bulkhead Solder For .086 Cable
ANO 2612-1034	QAM Straight Female Bulkhead Solder for 1.13mm/ 1.32mm/ 1.37mm Cable, Body: Albaloy Plated Brass
ANO 2612-1034-1	QAM Straight Female Bulkhead Solder for 1.13mm/ 1.32mm/ 1.37mm Cable, Body: Gold Plated Brass
ANO 2612-1034-2	QAM Straight Female Bulkhead Solder for 1.13mm/ 1.32mm/ 1.37mm Cable, Body: Passivated Stainless Steel
ANO 2612-1034-3	QAM Straight Female Bulkhead Solder for 1.13mm/ 1.32mm/ 1.37mm Cable, Body: Gold Plated Stainless Steel
ANO 2612-1100	QMA Straight Female Bulkhead Solder For .141 Cable
ANO 2612-3024	QMA Female Receptacle With Solder End, 4 Hole .500" SQ. Flange, Body: Gold Plated Brass
ANO 2612-3024-1	QMA Female Receptacle With Solder End, 4 Hole .500" SQ. Flange, Body: Albaloy Plated Brass
ANO 2612-5005	QMA Straight Female Solder less Panel Mount Screw On
ANO 2612-5047	QMA Female Bulkhead Front Mount, Screw On
ANO 2612-5050	QMA Receptacle Female, Waterproof, Bulkhead Mounted With Solder End
ANO 2621-2015	QMA Right Angle Male Crimp For RG316/RG174/LMR100
ANO 2621-2022	QMA Right Angle Male Solder For .141 Cable
ANO 2622-4035	QMA Right Angle Bulkhead Female PCB Receptacle, Body: Albaloy Plated Brass
ANO 2622-4035-1	QMA Right Angle Bulkhead Female PCB Receptacle, Body: Gold Plated Brass
ANO 3012-3001-1	TNCA Female, 4 Hole .689" SQ. Flange, Field Replaceable, Accept .015" Pin Dia.
ANO 3012-3001-2	TNCA Female, 4 Hole .689" SQ. Flange, Field Replaceable, Accept .018" Pin Dia.
ANO 3012-3001-3	TNCA Female, 4 Hole .689" SQ. Flange, Field Replaceable, Accept .020" Pin Dia.
ANO 3012-3001-4	TNCA Female, 4 Hole .689" SQ. Flange, Field Replaceable, Accept .036" Pin Dia.
ANO 3012-3002	TNCA Female 4 Hole .689" SQ. Flange Receptacle
ANO 3012-3004	TNCA Straight Female, 4 Hole .748" SQ. Flange Mount
ANO 3311-2102	TNC Straight Male Solder For PLEX-310, CXN3450, IW2801 Cable, Captivated Contact
ANO 3312-1104	TNC Straight Bulkhead Waterproof Female Solder for IW2801 / GORE 3450 / PLEX-310 Cable
ANO 3511-2002	ZMA Male(120→∞), 3 Slot, GT520 Cable
ANO 3512-4002	ZMA Female(120→∞), Edge Mount For .062 Board Thickness PCB, Receptacle,àITab Contact
ANO 5111-2034	N STRAIGHT MALE SOLDER FOR .141 CABLE CAPTIVATED CONTACT
ANO 5111-2153	N Straight Male Solder For IW1501 Cable, Captivated Contact
ANO 5111-2170	N Straight Male Solder for .086 Cable Captivated Contact
ANO 5111-2309	N Straight Male Solder for IW2801 / GORE 3450 / PLEX-310 Cable

18 GHz Products



ANO 5111-2354	N Straight Male Solder for IW1501 Cable, Captivated Contact
ANO 5111-3139	N Straight Male, 4 Hole 1.00" Sq. Flange Mount
ANO 5111-3306-1	N Straight Male, 4 Hole .687,Ä≥ SQ Flange to Accept .036
ANO 5111-3306-2	N Straight Male, 4 Hole .687,Ä≥ SQ. Flange to Accept .020
ANO 5111-3306-3	N Straight Male, 4 Hole .687,Ä≥ SQ. Flange to Accept .018
ANO 5111-3306-4	N Straight Male, 4 Hole .687,Ä≥ SQ. Flange to Accept .015
ANO 5112-2203	N Straight Female Solder For IW1501 Cable, Captivated Contact
ANO 5112-2336	N Straight Female Solder for IW 2801 / GORE 3450 / PLEX-310 Cable
ANO 5112-2348	N Straight Female Solder for AFLEX-141 Cable, Captivated Contact
ANO 5112-3187	N Straight Female, 4 Hole 1 inch SQ. Flange Mount
ANO 5112-3231-1	N Type Female, 4 Hole 1.00" SQ. Flange To Accept .036" Dia. Pin, Field Replaceable
ANO 5112-3231-2	N Type Female, 4 Hole 1.00" SQ. Flange To Accept .020" Dia. Pin, Field Replaceable
ANO 5112-3231-3	N Type Female, 4 Hole 1.00" SQ. Flange To Accept .018" Dia. Pin, Field Replaceable
ANO 5112-3231-4	N Type Female, 4 Hole 1.00" SQ. Flange To Accept .015" Dia. Pin, Field Replaceable
ANO 5112-3234-1	N-Type Female 4 Hole .687" SQ. Flange To Accept .036" Pin Dia.
ANO 5112-3234-2	N-Type Female 4 Hole .687" Sq Flange To Accept .020" Pin Dia.
ANO 5112-3234-3	N-Type Female 4 Hole .687" SQ. Flange To Accept .018" Pin Dia.
ANO 5112-3234-4	N-Type Female 4 Hole .687" SQ Flange To Accept .015" Pin Dia.
ANO 5112-3261-1	N-Type Female 4 Hole .500,Ä≥ SQ. Flange, Accept .036" Pin Dia., Field Replaceable
ANO 5112-3261-2	N-Type Female 4 Hole .500,Ä≥ SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 5112-3261-3	N-Type Female 4 Hole .500,Ä≥ SQ. Flange, Accept .018" Pin Dia., Field Replaceable
ANO 5112-3261-4	N-Type Female 4 Hole .500,Ä≥ SQ. Flange, Accept .015" Pin Dia., Field Replaceable
ANO 5121-2087	N Right Angle Male Crimp For RG142/RG223/RG400 Cable
ANO 5121-2320	N R/A Male Solder for PLEX-310 Cable
ANO 5311-2010	HPQN Straight Male Solder For .141 Cable, Center Contact: Gold Plated Brass
ANO 5311-2010-1	HPQN Straight Male Solder For .141 Cable, Center Contact: Silver Plated Brass
ANO 5311-2040	HPQN Straight Male Solder For ANO HF250 Cable
ANO 5311-2048	HPQN Straight Male Solder For SR086
ANO 5311-3054	HPQN Straight Male 4 Hole 1 inch SQ. Flange Receptacle, Threaded Post

18 GHz Products



ANO 5312-1032	HPQN Straight Waterproof Bulkhead Female Solder for RG402/.141 Cable
ANO 5321-2011	HPQN Right Angle Male Solder For .141 Cable
ANO 650-A1-H	7mm End Launch Connector High Profile, .015 Pin
ANO 6510-4003	7mm End Launch Connector, .010 Pin
ANO 6511-2001	7mm Straight Solder for PLEX-140 Cable, Captivated Contact
ANO 7311-2002	SMA Quick Locking Straight Male Solder for .141 Cable
ANO 9112-3027	SSMA 2 Hole Flange Mount Female Receptacle
ANO 9112-3046	SSMA Straight Female Solder Attachment 2 Hole Flange Stub Terminal, .328 inch Hole Spacing
ANO 9112-4045	SSMA Straight Female PCB Receptacle
ANO 9311-2013-1	SMP Straight Male 2 Hole Flange Mount Solder For .086 Cable, .327" Hole Spacing, Full Detent
ANO 9311-2013-2	SMP Straight Male 2 Hole Flange Mount Solder For .086 Cable, .327" Hole Spacing, Limited Detent
ANO 9311-2013-3	SMP Straight Male 2 Hole Flange Mount Solder For .086 Cable, .327" Hole Spacing, Smooth Bore
ANO 9311-2050-1	SMP Male Full Detent, 2 Hole Flange Mount For .047 S/R Cable, .282" Hole Spacing,
ANO 9311-2050-2	SMP Male Limited Detent, 2 Hole Flange Mount For .047 S/R Cable, .282" Hole Spacing,
ANO 9311-2050-3	SMP Male Smooth Bore, 2 Hole Flange Mount For .047 S/R Cable, .282" Hole Spacing
ANO 9311-3049-1	SMP Male Detent, 2 Hole Flange Mount, .481" Hole Spacing, EMI Gasket, Full Detent
ANO 9311-3049-2	SMP Male Detent, 2 Hole Flange Mount, .481" Hole Spacing, EMI Gasket, Limited Detent
ANO 9311-3049-3	SMP Male Detent, 2 Hole Flange Mount, .481" Hole Spacing, EMI Gasket, Smooth Bore
ANO 9311-3058-1	SMP Straight Male 4 Hole .354" SQ. Flange Panel Mount Receptacle, Full Detent
ANO 9311-3058-2	SMP Straight Male 4 Hole .354" SQ. Flange Panel Mount Receptacle, Limited Detent
ANO 9311-3058-3	SMP Straight Male Full Detent, 4 Hole .354" SQ. Flange Panel Mount Receptacle, Smooth Bore
ANO 9311-3059-1	SMP Straight Male Full Detent, 4 Hole .354" SQ. Flange Panel Mount Receptacle
ANO 9311-3059-2	SMP Straight Male Limited Detent, 4 Hole .354" SQ. Flange Panel Mount Receptacle
ANO 9311-3059-3	SMP Straight Male Smooth Bore, 4 Hole .354" SQ. Flange Panel Mount Receptacle
ANO 9311-3080-1	SMP Straight Full Detent Male, 4 Hole Flange Panel Mount Receptacle
ANO 9311-3080-2	SMP Straight Limited Detent Male, 4 Hole Flange Panel Mount Receptacle
ANO 9311-3080-3	SMP Straight Smooth Bore Male, 4 Hole Flange Panel Mount Receptacle
ANO 9311-3101-1	SMP Straight Male 4 Hole .315" SQ. Flange Panel Mount Receptacle, Full Detent
ANO 9311-3101-2	SMP Straight Male 4 Hole .315" SQ. Flange Panel Mount Receptacle, Limited Detent

18 GHz Products



ANO 9311-3101-3	SMP Straight Male 4 Hole .315" SQ. Flange Panel Mount Receptacle, Smooth Bore
ANO 9311-3135-1	SMP Straight Full Detent Male 2 Hole Flange Panel Mount Receptacle
ANO 9311-3135-2	SMP Straight Limited Detent Male 2 Hole Flange Panel Mount Receptacle
ANO 9311-3135-3	SMP Straight Smooth Bore Male 2 Hole Flange Panel Mount Receptacle
ANO 9311-4020-1	SMP Straight Male, PCB Receptacle, Full Detent
ANO 9311-4020-2	SMP Straight Male, PCB Receptacle, Limited Detent
ANO 9311-4020-3	SMP Straight Male, PCB Receptacle, Smooth Bore
ANO 9311-4020-4	SMP Straight Male, PCB Receptacle, Catcher's Mitt
ANO 9311-4024-1	SMP Straight Male, PCB Edge Mount, Full Detent
ANO 9311-4024-2	SMP Straight Male, PCB Edge Mount, Limited Detent
ANO 9311-4024-3	SMP Straight Male, PCB Edge Mount, Smooth Bore
ANO 9311-4064	SMP Plug Limited Detent Surface Mount, R/A Launch
ANO 9311-5125	SMP Straight FD Male Bulkhead Solder for .047 Cable
ANO 9312-2033	SMP Straight Female Solder For .141 Cable
ANO 9321-1112	SMP R/A Male Catchers Mitt Bulkhead Mount Solder For .086 Cable
ANO 9411-2060	SMPM Male Smooth Bore Interface Fit M38999 Size 12 Insert Solder for .086 Cable

ADAPTERS

Part Number	Description
ANO 141-931-1587-1	Adapter, BMA Male 4 Hole Flange Mount To SMP Full Detent Male
ANO 141-931-1587-2	Adapter, BMA Male 4 Hole Flange Mount To SMP Limited Detent Male
ANO 141-931-1587-3	Adapter, BMA Male 4 Hole Flange Mount To SMP Smooth Bore Male
ANO 141-941-1588-1	Adapter, BMA Male 4 Hole Flange Mount to SMPM Full Detent Male
ANO 141-941-1588-2	Adapter, BMA Male 4 Hole Flange Mount to SMPM Smooth Bore Male
ANO 142-142-1556	Adapter, BMA Female to BMA Female
ANO 201-212-1182	Adapter, Push-on SMA Male to SMA Female
ANO 201-212-1388	Adapter, Push-on SMA Male to SMA Female Bulkhead
ANO 211-211-1007	Adapter, SMA Male to SMA Male, Body: Nickel Plated Brass, Center Contact: Gold Plated Brass
ANO 211-211-1007-1	Adapter, SMA Male to SMA Male, Body: Gold Plated Brass, Center Contact: Gold Plated Brass
ANO 211-211-1007-2	Adapter, SMA Male to SMA Male, Body: Albaloy Plated Brass, Center Contact: Silver Plated Brass

18 GHz Products



ANO 211-211-2430	Adapter, Right Angle SMA Male To SMA Male
ANO 211-212-1066	Adapter, SMA Male To SMA Female
ANO 211-212-1302	Adapter, SMA Male to SMA Female
ANO 211-212-1520	Adapter, SMA Male To SMA Female
ANO 211-212-2097	Adapter, Right Angle, SMA Male To SMA Female, DC - 18 GHz, Body: Gold Plated Brass
ANO 211-212-2097-1	Adapter, Right Angle, SMA Male To SMA Female, DC - 18 GHz, Body: Albaloy Plated Brass
ANO 212-141-1408	Adapter, SMA Female To BMA Bulkhead Male
ANO 212-141-1583	Adapter, SMA Female to BMA Male, 2 Hole Flange Mount
ANO 212-142-1406	Floating Adapter, 0~1mm Min. Axial Float SMA Female to BMA Female, 2 Hole Flange Mount
ANO 212-212-1004	Adapter, SMA Female Bulkhead To SMA Female
ANO 212-212-1110	Adapter, SMA Female To SMA Female, 4 Hole Flange
ANO 212-212-1227	Adapter, Right Angle, SMA Female to SMA Female, Body: Gold Plated Brass
ANO 212-212-1227-1	Adapter, Right Angle, SMA Female to SMA Female, Body: Albaloy Plated Brass
ANO 212-212-1227-2	Adapter, Right Angle, SMA Female to SMA Female, Body: Passivated Stainless Steel
ANO 212-212-1258	Adapter, SMA Female To SMA Female
ANO 212-212-1370	Adapter, SMA Bulkhead Waterproof Female To SMA Female, Hermetic Seal
ANO 212-212-1390	Adapter, SMA Female to SMA Female, 4 Hole Flange, Body: Albaloy Plated Brass, Center Contact: Silver Plated Beryllium Copper Alloy
ANO 212-212-1390-1	Adapter, SMA Female to SMA Female, 4 Hole Flange, Body: Gold Plated Brass, Center Contact: Gold Plated Beryllium Copper Alloy
ANO 212-212-1537	Adapter, SMA Female to SMA Female, 2 Hole Flange, Body: Gold Plated Brass
ANO 212-212-1537-1	Adapter, SMA Female to SMA Female, 2 Hole Flange, Body: Passivated Stainless Steel
ANO 212-212-1571	Adapter, SMA Waterproof Female to SMA Female, 4 Hole Flange, Hermetic Seal
ANO 212-212-1591	Adapter, SMA Female to SMA Bulkhead Female 4 Hole Flange Mount, O-Ring Seal
ANO 212-931-1459-1	Adapter SMA Female 2 Hole Flange Mount To SMP Male Full Detent
ANO 212-931-1459-2	Adapter SMA Female 2 Hole Flange Mount To SMP Male Limited Detent
ANO 212-931-1459-3	Adapter SMA Female 2 Hole Flange Mount To SMP Male Smooth Bore
ANO 212-931-1531-1	Adapter SMA Female To SMP Male Full Detent, 2 Hole Flange Mount .450"
ANO 212-931-1531-2	Adapter SMA Female To SMP Male Limited Detent, 2 Hole Flange Mount .450"
ANO 212-931-1531-3	Adapter SMA Female To SMP Male Smooth Bore, 2 Hole Flange Mount .450"
ANO 212-931-1532	Adapter SMA Female 2 Hole Flange Mount To SMP Male Full Detent

18 GHz Products



ANO 212-931-1532-1	Adapter SMA Female 2 Hole Flange Mount To SMP Male Limited Detent
ANO 212-931-1532-2	Adapter SMA Female 2 Hole Flange Mount To SMP Male Smooth Bore
ANO 212-931-1533	Adapter SMA Female 4 Hole Flange Mount To SMP Male Full Detent
ANO 212-931-1533-1	Adapter SMA Female 4 Hole Flange Mount To SMP Male Limited Detent
ANO 212-931-1533-2	Adapter SMA Female 4 Hole Flange Mount To SMP Male Smooth Bore
ANO 212-931-1558	Adapter, Right Angle SMA Female to SMP Male (FD)
ANO 212-932-1519	Adapter, SMA Female 2 Hole Flange Mount to SMP Female
ANO 212-932-1561	Adapter, Right Angle SMA Female to SMP Female
ANO 212-941-1590-1	Adapter, SMA Female to SMPM Full Detent Male 4 Hole Flange Mount
ANO 212-941-1590-2	Adapter, SMA Female to SMPM Smooth Bore Male 4 Hole Flange Mount
ANO 261-211-1029	Adapter, QMA Male To SMA Male
ANO 261-212-1031	Adapter, QMA Male To SMA Female
ANO 261-261-1026	Adapter, QMA Male To QMA Male
ANO 261-262-1028	Adapter, QMA Male To QMA Female
ANO 261-511-1033	Adapter, QMA Male to N Male
ANO 261-512-1035	Adapter, QMA Male To N Female
ANO 262-211-1032	Adapter, QMA Female To SMA Male
ANO 262-212-1030	Adapter, QMA Female To SMA Female
ANO 262-212-1070	Adapter QMA Female To SMA Waterproof Bulkhead Female
ANO 262-212-1162	Adapter, QMA Waterproof Bulkhead Female To SMA Female
ANO 262-262-1027	Adapter, QMA Female To QMA Female
ANO 262-262-1272	Adapter, QMA Bulkhead Female To QMA Female
ANO 262-262-1272-1	Adapter, QMA Bulkhead Female To QMA Female, Bold: Gold Plated Brass
ANO 262-262-1272-2	Adapter, QMA Bulkhead Female To QMA Female, Passivated Stainless Steel 303
ANO 262-511-1036	Adapter, N Male To QMA Female
ANO 262-512-1034	Adapter QMA Female To N Female
ANO 332-212-1402-1	Adapter, TNC Bulkhead Waterproof Female to SMA Female, Body: Passivated Stainless Steel
ANO 332-212-1402-2	Adapter, TNC Bulkhead Waterproof Female to SMA Female, Body: Nickel Plated Brass
ANO 511-211-1121	Adapter, N Male To SMA Male

18 GHz Products



ANO 511-211-1121-1	Adapter, N Male To SMA Male
ANO 511-211-1191	Adapter, N Male To SMA Male
ANO 511-211-1255	Adapter, N Male To SMA Male
ANO 511-211-1451	Adapter, N Male to SMA Male, 4 Hole Flange
ANO 511-212-1024	Adapter, N Male To SMA Female, Nickel Plated Brass
ANO 511-212-1024-1	Adapter, N Male To SMA Female, Body: Albaloy Plated Brass
ANO 511-212-1116	Adapter, N Male To SMA Female
ANO 511-212-1116-1	Adapter, N Male To SMA Female
ANO 511-212-1192	Adapter, N Male To SMA Female
ANO 511-212-1416	Adapter, N Male To SMA Female
ANO 511-511-1009	Adapter, N Male To N Male
ANO 511-511-1462	Adapter, N Male To N Male
ANO 511-511-1462-1	Adapter, N Male To N Male
ANO 511-512-1103	Adapter, N Male To N Female
ANO 511-512-1329	Adapter, N Male To N Female Bulkhead
ANO 511-512-1427	Adapter, N Male To N Female
ANO 511-512-1427-1	Adapter, N Male To N Female
ANO 511-512-1503	Adapter, N Female To Push-On N Male
ANO 512-211-1232	Adapter, N Female To SMA Male
ANO 512-211-1429	Adapter, N Female to SMA Male
ANO 512-211-1441	Adapter, N Female To SMA Male, 4 Hole Flange
ANO 512-211-1442	Adapter, N Female to SMA Male, 4 Hole Flange
ANO 512-211-1450	Adapter, N Female to SMA Male, 4 Hole Flange
ANO 512-212-1003	Adapter, N Straight Waterproof Bulkhead Female To SMA Female
ANO 512-212-1025	Adapter, N Female To SMA Female
ANO 512-212-1112	Adapter, N Female To SMA Female, 4 Hole Flange
ANO 512-212-1112-1	Adapter, N Female to SMA Female, 4 Hole Flange, Body: Albaloy Plated Brass
ANO 512-212-1112-2	Adapter, N Female to SMA Female, 4 Hole Flange, Body: Passivated Stainless Steel
ANO 512-212-1186	Adapter, N Female To SMA Female Waterproof, 4 Hole Flange

18 GHz Products



ANO 512-212-1193	Adapter, N Female To SMA Female
ANO 512-212-1256	Adapter, N Female To SMA Female, Body: Nickel Plated Brass, Center Contact: Gold Plated Beryllium Copper Alloy
ANO 512-212-1256-1	Adapter, N Female To SMA Female, Body: Albaloy Plated Brass, Center Contact: Silver Plated Beryllium Copper Alloy
ANO 512-212-1307	Adapter, N Female to SMA Female, 4 Holes Flange
ANO 512-212-1426	Adapter, N Female To SMA Female
ANO 512-212-1447	Adapter, N Straight Waterproof Bulkhead Female to SMA Female
ANO 512-302-1458	Adapter, N Straight Bulkhead Female To TNCA Female
ANO 512-511-1553	Adapter, N Female to Push-on N Male
ANO 512-512-1320	Adapter, N Female To N Female, Body: Nickel Plated Brass
ANO 512-512-1320-1	Adapter, N Female To N Female, Albaloy Plated Brass
ANO 512-512-1560	Adapter, N Female to S Female
ANO 531-511-1044	Adapter, HPQN Male To N Male
ANO 531-512-1046	Adapter, HPQN Male To N Female
ANO 531-531-1037	Adapter, HPQN Male To HPQN Male
ANO 531-532-1039	Adapter, HPQN Male To HPQN Female
ANO 532-511-1047	Adapter, HPQN Female To N Male
ANO 532-511-1405	Adapter, HPQN Female Bulkhead To N Female
ANO 532-512-1045	Adapter, HPQN Female To N Female
ANO 532-532-1038	Adapter, HPQN Female To HPQN Female
ANO 741-211-1547	Adapter, M10(NEX10) Male to SMA Male
ANO 741-212-1518	Adapter, M10(NEX10) Male To SMA Female
ANO 742-211-1548	Adapter, M10(NEX10) Female to SMA Male
ANO 742-212-1549	Adapter, M10(NEX10) Female to SMA Female
ANO 912-912-1440	Adapter, SSMA Bulkhead Waterproof Female To SSMA Female
ANO 931-212-1504	Adapter, SMP Waterproof Bulkhead Male To SMA Female
ANO 932-932-1287	Adapter, SMP Female To SMP Female, L= 12.35
ANO 932-932-1409	Adapter, SMP Spring Loaded Female To SMP Female, Uncompressed Length=15.44 [.608]
ANO 932-932-1409-1	Adapter, SMP Spring Loaded Female To SMP Female, Uncompressed Length=16.54 [.651]
ANO 932-932-1409-2	Adapter, SMP Spring Loaded Female To SMP Female, Uncompressed Length=20.70 [.815]

18 GHz Products



ANO 932-932-1443	Adapter, SMP Spring Loaded Female to SMP Female, Uncompressed Length=12.88[.507]
ANO 932-932-1461	Adapter, SMP Spring Loaded Female to SMP Female, Uncompressed Length=16.83 [.663]
ANO 932-932-1464	Adapter, SMP Spring Loaded Female to SMP Female, Uncompressed Length=18.92 [.745]
PA2921K	Precision Adapter, Right Angle 2.92mm Male to SMA Female
PA3021A	Precision Adapter TNCA Male To SMA Male
PA3021B	Precision Adapter TNCA Male To SMA Female
PA3021C	Precision Adapter TNCA Female To SMA Female
PA3021D	Precision Adapter TNCA Female To SMA Male
PA3021EB	Precision Adapter, TNC Bulkhead Female to SMA Female
PA3021F	Precision Adapter, TNCA Female To SMA Female 4 Hole Flange
PA3030A	Precision Adapter , TNCA Male To TNCA Male
PA3030B	Precision Adapter, TNCA Male To TNCA Female
PA3030C	Precision Adapter , TNCA Female To TNCA Female
PA3030K	Precision Adapter, Right Angle TNCA Male to TNCA Female
PA5121A	Precision Adapter, N Male To SMA Male
PA5121B	Precision Adapter, N Male To SMA Female
PA5121C	Precision Adapter, N Female To SMA Female
PA5121D	Precision Adapter, N Straight Female To SMA Male
PA5121E	Precision Adapter, N Straight Waterproof Bulkhead Female To SMA Female
PA5121EA	Precision Adapter, N Female to SMA Bulkhead Female
PA5121F	Precision Adapter, N Female to SMA Female, 4 Holes Flange
PA5122A	Precision Adapter 2.4mm Male To N Male
PA5122B	Precision Adapter 2.4mm Female To N Male
PA5122C	Precision Adapter 2.4mm Female To N Female
PA5122CA	Precision Adapter, 2.4mm Female To N Female, VSWR 1.08 MAX.
PA5122D	Precision Adapter 2.4mm Male To N Female
PA5125A	Precision Adapter N Male To 3.5mm Male
PA5125B	Precision Adapter N Male To 3.5mm Female
PA5125C	Precision Adapter N Female To 3.5mm Female

18 GHz Products



PA5125D	Precision Adapter N Female To 3.5mm Male
PA5129A	Precision Adapter, 2.92mm Male To N Male
PA5129B	Precision Adapter, 2.92mm Female To N Male
PA5129C	Precision Adapter, 2.92mm Female To N Female
PA5129D	Precision Adapter, 2.92mm Male To N Female
PA5130A	Precision Adapter, TNCA Male To N Male
PA5130B	Adapter, N Male To TNC Female
PA5130C	Precision Adapter, TNCA Female To N Female
PA5130D	Precision Adapter, TNCA Male To N Female
PA5130F	Precision Adapter, TNCA Female To N Female 4 Hole Flange
PA5151A	Precision Adapter , N Male To N Male
PA5151B	Precision Adapter , N Male To N Female
PA5151C	Precision Adapter , N Female To N Female
PA5151E	Precision Adapter N Female Bulkhead To N Female
PA5151EA	Precision Adapter, N Female Bulkhead to N Female
PA5151F	Precision Adapter, N Female To N Female 4 Hole Flange
PA5151I	Precision Adapter , N Female Waterproof To N Male 4 Hole Flange
PA5151J	Precision Adapter, Right Angle, N Male to N Male
PA5151K	Precision Adapter, N Right Angle Male To N Female
PA5151L	Precision Adapter, Right Angle, N Female to N Female
PA6525A	Adapter, 7mm Sexless To 3.5mm Female
PA6525B	Adapter, 7mm Sexless To 3.5mm Male
PA6551A	Precision Adapter, 7mm Sexless to N Female
PA6551B	Precision Adapter, 7mm Sexless to N Male
PA6565A	Adapter, 7mm Sexless To 7mm Sexless
PA6571A	Precision Adapter, 7mm Sexless to NMD3.5mm Female
PA6571B	Precision Adapter, 7mm Sexless to NMD3.5mm Male
PA7151A	Precision Adapter, NMD3.5mm Male to N Male
PA7151C	Precision Adapter, NMD3.5mm Female to N Female

18 GHz Products



PA7151D	Precision Adapter, NMD3.5mm Female to N Male
-------------------------	--

CABLES

Part Number	Description
-------------	-------------

PA3030E	Precision Adapter, TNCA Female to TNCA Female 4 Hole Bulkhead Mount
-------------------------	---

AFLEX-250	AFLEX Series Cable, AFLEX-250 with FEP Jacket
---------------------------	---

ANO HF047	Hand-Formable Series Cable, ANO HF047 with Tin Soaked Copper Braid Outer Conductor
---------------------------	--

ANO HF047FEP	Hand-Formable Series Cable, ANO HF047FEP with FEP Jacket
------------------------------	--

ANO HF086	Hand-Formable Series Cable, ANO HF086 with Tin Soaked Copper Braid Outer Conductor
---------------------------	--

ANO HF086-LL	Low Loss Hand-Formable Series Cable, ANO HF86-LL with Tin Soaked Copper Braid Outer Conductor
------------------------------	---

ANO HF086FEP	Hand-Formable Series Cable, ANO HF086FEP with FEP Jacket
------------------------------	--

ANO HF141	Hand-Formable Series Cable, ANO HF141 with Tin Soaked Copper Braid Outer Conductor
---------------------------	--

ANO HF141FEP	Hand-Formable Series Cable, ANO HF141FEP with FEP Jacket
------------------------------	--

ANO HF141FEP(W)	Hand-Formable Series Cable, ANO HF141FEP(W) with White FEP Jacket
---------------------------------	---

ANO HF250	Hand-Formable Series Cable, ANO HF250 with Tin Soaked Copper Braid Outer Conductor
---------------------------	--

ANO HF250FEP	Hand-Formable Series Cable, ANO HF250FEP with FEP Jacket
------------------------------	--

ANO HF250FEP(W)	Hand-Formable Series Cable, ANO HF250FEP(W) with White FEP Jacket
---------------------------------	---

EP090	EP Series Cable, EP090 with FEP Jacket
-----------------------	--

EP200	EP Series Cable, EP200 with TPU Jacket
-----------------------	--

PLEX059	PLEX Series Cable, PLEX059 With Blue FEP Jacket
-------------------------	---

PLEX310-lite	PLEX-lite Series Cable, PLEX310-lite with eTFE Jacket
------------------------------	---

PLEX320	PLEX Series Cable, PLEX320 With Gray FEP Jacket
-------------------------	---

PLEX320VB	PLEX Series Cable, PLEX320VB With Black PFA Jacket
---------------------------	--

PLEX310VT	PLEX Series Cable, PLEX310VT With Violet (PANTONE 2583C) FEP Jacket
---------------------------	---

RG401	RG Series Semi-rigid Cable, 50 Ohm, with Copper Tube
-----------------------	--

SR250	Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube
-----------------------	--

SR250 AL/TP	Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube
-----------------------------	--

CABLE ASSEMBLIES

Part Number	Description
-------------	-------------

AF047-SMPMF-SMPMF-3	Cable Assembly, SMPM Straight Female to VITA670.1 Plug-in Contact SMPM Straight Female, AFLEX-047 Cable, 3 Inches
-------------------------------------	---

18 GHz Products



AF086-NRP-SMAM-6	Cable Assembly, NanoRF Pin to SMA Straight Male, ANO AFLEX-086 Cable, 6 Inches
AF086-SMAM-QMAM-59	Cable Assembly, SMA Straight Male To QMA Straight Male, AFLEX-086 Cable, 59 inches
AF086-SMAM-SMAM-12	Cable Assembly, SMA Straight Male To SMA Straight Male, AFLEX-086 Cable, 12 inches
AF086-SMAM-SMPF-51	Cable Assembly, SMA Straight Male To SMP Straight Female, AFLEX-086 Cable, 51 inches
AF086-SMPM-TF-SMAM-15	Cable Assembly, SMPM-T Female To SMA Male, AFLEX-086 Cable, L=381.00 \pm 5 [15 \pm .197]
AF086-SMPM-TF-SMAM-26	Cable Assembly, SMPM-T Female To SMA Male, AFLEX-086 Cable, L=660.4 \pm 8 [26 \pm .315]
AF086-SMPM-TF-SMAM-35	Cable Assembly, SMPM-T Female To SMA Male, AFLEX-086 Cable, L=889.0 \pm 8 [35 \pm .315]
AF141-NM-NLM-12	Cable Assembly, N Straight Male To N R/A Male, AFLEX-141 Cable, 12 Inches
AF141-NM-SMAM-39	Cable Assembly, N Straight Male To SMA Straight Male, AFLEX-141 Cable, 39 Inches
HF086-SMAM-SMAFBW-10	Cable Assembly, SMA Straight Male To SMA Straight Bulkhead Waterproof Female ANO HF086 Cable, 10 Inches
HF086-SMAM-SMAM-10	Cable Assembly, SMA Straight Male To SMA Straight Male, ANO HF086 Cable, 10 Inches
HF086-SMAM-SMPF-15	Cable Assembly, SMA Straight Male To SMP Straight Female, ANO HF086 Cable, 15 Inches
HF141-NM-NM-XX	Cable Assembly, N Straight Male To N Straight Male, ANO HF141 Cable
HF141-QMAM-QMALM-XX	Cable Assembly, QMA Straight Male To QMA Right Angle Male, ANO HF141 Cable
HF141-QMAM-SMAM-XX	Cable Assembly, QMA Straight Male To SMA Straight Male, ANO HF141 Cable
HF141-SMALM-NF4HF-XX	Cable Assembly, SMA Right Angle Male To N Straight Female 4 Hole Flange, ANO HF141 Cable
HF141-SMALM-NFBW-XX	Cable Assembly, SMA Right Angle Male To N Straight Female Bulkhead Waterproof, ANO HF141 Cable
HF141-SMALM-SMALM-XX	Cable Assembly, SMA Right Angle Male To SMA Right Angle Male, ANO HF141 Cable
HF141-SMAM-NF4HF-XX	Cable Assembly, SMA Straight Male To N Straight Female 4 Hole Flange, ANO HF141 Cable
HF141-SMAM-NFBW-XX	Cable Assembly, SMA Straight Male To N Straight Female Bulkhead Waterproof, ANO HF141 Cable
HF141-SMAM-SMA4HF-XX	Cable Assembly, SMA Straight Male To SMA Straight Female Flange 4 Hole , ANO HF141 Cable
HF141-SMAM-SMALM-XX	Cable Assembly, SMA Straight Male To SMA Right Angle Male, ANO HF141 Cable
HF141-SMAM-SMAM-XX	Cable Assembly, SMA Straight Male To SMA Straight Male, ANO HF141 Cable
HF141-SMAM-SMPF-XX	Cable Assembly, SMA Straight Male To SMP Straight Female, ANO HF141 Cable
HF141-SMPF-NF4HF-XX	Cable Assembly, SMP Straight Female To N Straight Female 4 Hole Flange, ANO HF141 Cable
HF141-SMPF-NM-XX	Cable Assembly, SMP Straight Female To N Straight Male, ANO HF141 Cable
HF141-SMPF-SMALM-XX	Cable Assembly, SMP Straight Female To SMA Right Angle Male, ANO HF141 Cable
HF141-SMPLF-NF4HF-XX	Cable Assembly, SMP Right Angle Female To N Straight Female 4 Hole Flange, ANO HF141 Cable
HF141-SMPLF-NM-XX	Cable Assembly, SMP Right Angle Female To N Straight Male, ANO HF141 Cable

18 GHz Products



PLEX090-SMAM-SMAM-20CM	Cable Assembly, SMA Straight Male to SMA Straight Male, PLEX090 Cable, 20cm
PLEX140-7MM-29LM-50CM	Cable Assembly, 7mm Straight to 2.92mm R/A Male for PLEX140 Cable, 0.5 Meters
PLEX220-SMAM-SMAM-500MM-PM	Cable Assembly, SMA Straight Male to SMA Straight Male, PLEX220 Cable, 500mm
PT-NM-NM-396	PT Cable Assembly, N Straight Male to N Straight Male connector, PLEX-130P, 396 inches
PT-NM-NM-60	PT Cable Assembly, N Straight Male to N Straight Male connector, PLEX-130P, 60 inches
PT-SMAM-NM-26	26 INCHES CABLE , SMA (M) TO N(M) CONNECTOR
SR086-SMAM-SMAM-1	Cable Assembly, SMA Straight Male To SMA Straight Male, ANO SR086 Cable, 1 Inches
SR141-SMAM-SMAM-5	Cable Assembly, SMA Straight Male To SMA Straight Male, ANO SR141 Cable, 5 Inches

TERMINATIONS

Part Number	Description
ANO 714-201	Coaxial Termination BMA Female, 1 Watt, DC-18 GHz
ANO 721-102	Coaxial Termination, SMA Male, 2 Watt, DC-18GHz
ANO 721-104	Coaxial Termination, SMA Male, 5 Watts, DC~18GHz
ANO 721-115	Coaxial Termination, SMA Male, 10 Watts, DC-18GHz
ANO 721-117	Coaxial Termination, SMA Male, 1 Watt, DC-18 GHz
ANO 721-120	Coaxial Termination, SMA Male, 10 Watts, DC-18GHz
ANO 721-128	Coaxial Termination, SMA Male, 0.5 Watt, DC-18GHz
ANO 721-133	Coaxial Termination, SMA Male, 20 Watts, DC-18GHz
ANO 721-138	Coaxial Termination, SMA Male, 50 Watts, DC-18 GHz
ANO 721-206	Coaxial Termination SMA Female, 2 Watt, DC~18GHz
ANO 721-207	Coaxial Termination, SMA Female, 5 Watts, DC-18GHz
ANO 721-208	Coaxial Termination, SMA Female, 5 Watts, DC-18GHz
ANO 721-211	Coaxial Termination, SMA Female, 2 Watts, DC-18GHz
ANO 721-227	Coaxial Termination, SMA Female, 15 Watts, DC-18GHz
ANO 726-101	Coaxial Termination, QMA Male 1 Watt, DC-18GHz
ANO 726-109	Coaxial Termination, QMA Male 5 Watts, DC-18 GHz
ANO 730-101	Coaxial Termination, TNCA Male, 2 Watts, DC~18 GHz
ANO 730-102	Coaxial Termination, TNC Male 5 Watts, DC-18 GHz
ANO 730-105	Coaxial Termination, TNCA Male 2 Watts With Chain, DC-18GHz

18 GHz Products



ANO 730-112	Coaxial Termination, TNCA Male, 2 Watts, DC-18 GHz
ANO 730-113	Coaxial Termination, TNCA Male 2 Watts With Chain, DC-18 GHz
ANO 730-203	Coaxial Termination, TNCA Female, 2Watts, DC-18GHz
ANO 751-101	Coaxial Termination, N Male 2 Watts, DC~18GHz
ANO 751-102	Coaxial Termination, N Male, 2 Watts, DC-18GHz
ANO 751-130	Coaxial Termination, N Male 5 Watts, DC-18GHz
ANO 751-138	Coaxial Termination, Type S Male, 2 Watts, DC-18GHz
ANO 751-210	Coaxial Termination N Male 2 Watts, DC~18GHz, Body: Passivated Stainless Steel
ANO 751-246	Coaxial Termination, N Female, 2 Watts, DC-18 GHz, Body: Albaloy Plated Brass
ANO 751-246-1	Coaxial Termination, N Female, 2 Watts, DC-18 GHz, Body: Passivated Stainless Steel
ANO 794-205	Coaxial Termination, SMPM Female , 0.25 Watts, DC-18GHz
ANO 794-206	Coaxial Termination, SMPM Female, 0.5 Watts, DC-18 GHz

ATTENUATORS

Part Number	Description
ANO 21-0201-01	1 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-02	2 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-03	3 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-04	4 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-05	5 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-06	6 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-07	7 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-08	8 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-09	9 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-10	10 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-15	15 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-20	20 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-25	25 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0201-30	30 dB Attenuator, SMA Male To SMA Female 2 Watt, DC-18GHz
ANO 21-0209-31	31 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz

18 GHz Products



ANO 21-0209-32	32 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-33	33 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-34	34 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-35	35 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-36	36 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-37	37 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-38	38 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-39	39 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0209-40	40 dB Attenuator, SMA Male to SMA Female 2 Watt, DC-27 GHz
ANO 21-0210-00	0 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-01	1 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-02	2 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-03	3 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-04	4 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-05	5 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-06	6 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-07	7 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-08	8 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-09	9 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-10	10 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-15	15 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0210-20	20 dB Attenuator, SMA Male to SMA Female, 2 Watts Uni Directional, DC-18 GHz
ANO 21-0502-07	7 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-0502-08	8 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-0502-09	9 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-0502-10	10 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-0502-20	20 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-0502-30	30 dB Attenuator, SMA Male to SMA Female, 5 Watts, DC-18 GHz
ANO 21-1002-01	1 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz

18 GHz Products



ANO 21-1002-02	2 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-03	3 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-04	4 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-05	5 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-06	6 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-07	7 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-08	8 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-09	9 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-10	10 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-15	15 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-20	20 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-25	25 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1002-30	30 dB Attenuator, SMA Male To SMA Female 10 Watt, DC-18GHz
ANO 21-1003-01	1 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-02	2 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-03	3 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-04	4 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-05	5 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-06	6 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-07	7 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-08	8 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-09	9 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-10	10 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-15	15 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-20	20 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-25	25 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-30	30 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-35	35 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz
ANO 21-1003-40	40 dB Attenuator SMA Male to SMA Female, 10 Watts, DC-18 GHz

18 GHz Products



ANO 21-1004-01	1 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-02	2 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-03	3 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-04	4 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-05	5 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-06	6 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-07	7 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-08	8 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-09	9 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-10	10 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-15	15 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-20	20 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-25	25 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-30	30 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-35	35 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1004-40	40 dB Attenuator, SMA Male to SMA Female, 10 Watts, DC-27 GHz
ANO 21-1502-03	3 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-04	4 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-05	5 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-06	6 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-07	7 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-08	8 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-09	9 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-10	10 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-20	20 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-30	30 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-1502-40	40 dB Attenuator, SMA Male to SMA Female, 15 Watts, DC-18 GHz
ANO 21-2502-03	3 dB Attenuator, SMA Female to SMA Female, 25 Watts, DC-18 GHz
ANO 21-5002-10	10 dB Attenuator, SMA Male to SMA Female, 50 Watts, DC-18 GHz

18 GHz Products



ANO 21-5002-20	20 dB Attenuator, SMA Male to SMA Female, 50 Watts, DC-18 GHz
ANO 21-5002-30	30 dB Attenuator, SMA Male to SMA Female, 50 Watts, DC-18 GHz
ANO 21-5002-40	40 dB Attenuator, SMA Male to SMA Female, 50 Watts, DC-18 GHz
ANO 51-0201-01	1 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-02	2 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-03	3 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-04	4 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-05	5 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-06	6 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-07	7 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-08	8 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-09	9 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-10	10 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-15	15 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-20	20 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-25	25 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0201-30	30 dB Attenuator, N Male To N Female, 2W, DC-18GHz
ANO 51-0204-10	10 dB Attenuator, N Male to N Female, DC-18 GHz, 2 W
ANO 51-0204-20	20 dB Attenuator, N Male to N Female, DC-18 GHz, 2 W
ANO 51-0204-30	30 dB Attenuator, N Male to N Female, DC-18 GHz, 2 W
ANO 51-0503-01	1 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-02	2 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-03	3 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-04	4 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-05	5 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-06	6 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-07	7 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-08	8 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-09	9 dB Attenuator N Male to N Female, 5W, DC-18GHz

18 GHz Products



ANO 51-0503-10	10 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-15	15 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-20	20 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-25	25 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-30	30 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-35	35 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-0503-40	40 dB Attenuator N Male to N Female, 5W, DC-18GHz
ANO 51-1002-01	1 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-02	2 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-03	3 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-04	4 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-05	5 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-06	6 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-07	7 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-08	8 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-09	9 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-10	10 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-15	15 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-20	20 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-25	25 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-30	30 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-35	35 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-1002-40	40 dB Attenuator, N Male to N Female, 10W, DC-18 GHz
ANO 51-20003-06	6 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz
ANO 51-20003-07	7 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz
ANO 51-20003-08	8 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz
ANO 51-20003-09	9 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz
ANO 51-20003-10	10 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz
ANO 51-20003-20	20 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz

18 GHz Products



[ANO 51-20003-30](#) 30 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz

[ANO 51-20003-40](#) 40 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz

[ANO 51-20003-50](#) 50 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz

[ANO 51-20003-60](#) 60 dB Attenuator, N Male to Female 200 Watts Suni Directional, DC-18 GHz

[ANO 51-2001-01](#) 1 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-02](#) 2 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-03](#) 3 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-04](#) 4 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-05](#) 5 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-06](#) 6 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-07](#) 7 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-08](#) 8 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-09](#) 9 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-10](#) 10 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-15](#) 15 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-20](#) 20 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-25](#) 25 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2001-30](#) 30 dB Attenuator N Male to N Female, 20W, DC-18GHz

[ANO 51-2002-01](#) 1 dB Attenuator, N Male to N Female, 20W, DC-18 GHz

[ANO 51-2002-02](#) 2 dB Attenuator, N Male to N Female, 20W, DC-18 GHz

[ANO 51-2002-03](#) 3 dB Attenuator, N Male to N Female, 20W, DC-18 GHz

[ANO 51-2501-20](#) 20 dB Attenuator N Male to N Female, 25W, DC-18 GHz

[ANO 51-2501-30](#) 30 dB Attenuator N Male to N Female, 25W, DC-18 GHz

[ANO 51-2501-40](#) 40 dB Attenuator N Male to N Female, 25W, DC-18 GHz

[ANO 51-2501-50](#) 50 dB Attenuator N Male to N Female, 25W, DC-18 GHz

[ANO 51-5001-10](#) 10 dB Attenuator, N Male to N Female, 50W, DC-18 GHz

[ANO 51-5001-15](#) 15 dB Attenuator, N Male to N Female, 50W, DC-18 GHz

[ANO 51-5001-20](#) 20 dB Attenuator, N Male to N Female, 50W, DC-18 GHz

[ANO 51-5001-30](#) 30 dB Attenuator, N Male to N Female, 50W, DC-18 GHz

18 GHz Products



ANO 51-5002-10	10 dB Attenuator, N Male to N Female, DC- 18 GHz, 50 W
ANO 51-5002-20	20 dB Attenuator, N Male to N Female, DC- 18 GHz, 50 W
ANO 51-5002-30	30 dB Attenuator, N Male to N Female, DC- 18 GHz, 50 W
ANO 51-5002-40	40 dB Attenuator, N Male to N Female, DC- 18 GHz, 50 W

TOOLS

Part Number	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque=8±0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12±0.48 in.lbs, Hex Size =5/16 in.
ANO TW-003	Torque Wrench For N Type Connectors, Preset Torque= 8±0.32 in.lbs; Hex Size=3/4 in.
ANO TW-004	Torque Wrench for N/ 7 mm Type Connectors, Preset Torque= 14±0.56 in.lbs, Hex Size =3/4 in.
ANO TW-005	Torque Wrench for N Type Connectors, Preset Torque= 8±0.32 in.lbs, Hex Size = 25/32 in.
ANO TW-006	Torque Wrench for N Type Connectors, Preset Torque= 14±0.56 in.lbs, Hex Size=25/32 in.
ANO TW-007	Torque Wrench for N Type Connectors, Preset Torque= 8±0.32 in.lbs, Hex Size =13/16 in.
ANO TW-008	Torque Wrench for SC/N Type Connectors, Preset Torque= 14±0.56 in.lbs, Hex Size =13/16 in.
ANO TW-039	Torque Wrench for N Type Connectors Preset Torque=1.36±0.05 Nm [12±0.52 in.lbs] Hex Size 20mm [25/32 in.]
ANO TW-040	Torque Wrench Preset Torque= 1.36±0.05 Nm [12±0.48 in.lbs] Hex Size 18 mm [.71 in.]
ANO TW-026	Torque Wrench for N/7mm Type Connectors, Preset Torque= 1.36±0.05 NM [12±0.48 In .lbs], Hex Size 19.1 mm [3/4 in.]
ANO TW-025	Torque Wrench for N Type & 7mm Connectors, Preset Torque= 2.26±0.09 NM [20±0.8 in.bls], Hex Size 19.1mm [3/4 in.]
ANO TW-013	Torque Wrench for SSMA Type Connectors, Preset Torque= 5.0±0.2 in. lbs, Hex Size =1/4 in.
ANO TW-014	Torque Wrench for SSMA Type Connectors, Preset Torque= 8±0.32 in.lbs, Hex Size =1/4 in.
ANO TW-019	Torque Wrench for SMA Type Connectors, Preset Torque= 5±0.2 in.lbs, Hex Size =5/16 in.
ANO TWSD-001	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9±0.04 NM [8±0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue
T29002-1	Fixed Wrench for Bulkhead 2.92mm/SMA Connectors (Hex 11mm)

ACCESSORIES

Part Number	Description
ANO 2111-6099	Cap, Male With Chain for SMA, 3.5mm, 2.92mm
ANO 2111-6100	SMA Cap, Male Without Chain
ANO 2112-6101	SMA Cap, Female With Chain

18 GHz Products



ANO 2112-6102	SMA Cap, Female Without Chain
ANO 2611-6044	QMA CAP, MALE WITHOUT CHAIN
ANO 2611-6053	QMA CAP, MALE WITH CHAIN
ANO 3311-6074	TNC CAP, MALE WITH CHAIN
ANO 3312-6068	TNC CAP, FEMALE WITH CHAIN