

40 GHz Products



CONNECTORS

Product Name	Description
ANO 291-A1-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 291-A1-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 291-A2-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 291-A2-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 291-A3-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 291-A3-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 291-A4-H	2.92mm Male End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 291-A4-L	2.92mm Male End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 2911-2029	2.92mm Straight Male Solder for UT-085/UT-085C-Form Cable Captivated Contact
ANO 2911-2040	2.92mm Straight Male Solder For UT-085C-LL Cable Captivated Contact
ANO 2911-2070	2.92mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 2911-2088-PT	2.92mm Straight Male Solder for PLEX130P Cable, Captivated Contact
ANO 2911-2091	2.92mm Straight Male Solder For PLEX-140 Cable Captivated Contact
ANO 2911-2095	2.92mm Straight Male Solder For 047SC-2901 Cable
ANO 2911-2097	2.92mm Straight Male Solder For UT-47 Cable, Solder Direct
ANO 2911-2108	2.92mm Straight Male Solder For SR141/RG402 Cable, Captivated Contact
ANO 2911-2120	2.92mm Straight Male Solder for PLEX-090D Cable, Captivated Contact
ANO 2911-2122	2.92mm Straight Male Solder for SR120LL Cable, Captivated Contact
ANO 2911-2129	2.92mm Straight Male Solder for AFLEX-141 Cable, Captivated Contact
ANO 2911-2141	2.92mm Straight Male Solder for AFLEX-086 Cable, Captivated Contact
ANO 2911-3013-1	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3013-2	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3013-3	2.92mm Straight Male, 4 Holes .374" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3026-1	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3026-2	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3026-3	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2911-3026-4	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .018" Pin Dia., Field Replaceable

40 GHz Products



ANO 2911-3026-5	2.92mm Straight Male, 4 Holes .500" SQ. Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3053-1	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3053-2	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3053-3	2.92mm Straight Male, 2 Holes .551" Long Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3054-1	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 2911-3054-2	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 2911-3054-3	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .020" Pin Dia., Field Replaceable
ANO 2911-3054-4	2.92mm Straight Male, 2 Holes .625" Long Flange, Accept .015" Pin Dia., Field Replaceable
ANO 2911-3143	2.92mm Male, 4 Hole Flange Mount Extended Dielectric, Post Contact
ANO 2911-3171	2.92mm Male, 2 Hole Flange Mount, Post Contact
ANO 2911-5056-1	2.92mm Straight Male Thread-in To Accept .009 Pin Dia.
ANO 2911-5056-2	2.92mm Straight Male Thread-in To Accept .012 Pin Dia.
ANO 2911-5056-3	2.92mm Straight Male Thread-in To Accept .020 Pin Dia.
ANO 2911-5064	2.92mm Straight Male Thread-in To Accept .020 Pin Dia.
ANO 2912-1034	2.92mm Straight Bulkhead Female Solder for .086 Cable, Captivated Contact
ANO 2912-1110	2.92mm Straight Bulkhead Female Solder for .086 Cable, Captivated Contact
ANO 2912-1113	2.92mm Straight Bulkhead Female Solder for .141 Cable, Captivated Contact
ANO 2912-1121	2.92mm Straight Female, Bulkhead, Solder for SR120LL Cable
ANO 2912-1145	2.92mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 2912-1149	2.92mm Straight Bulkhead Waterproof Female Solder for PLEX-140 Cable, Captivated Contact
ANO 2912-1152	2.92mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 2912-1158	2.92mm Straight Female, Bulkhead Solder for .141 Cable
ANO 2912-2078	2.92mm Straight Female Solder For IW1501/Plex-140 Cable, Captivated Contact
ANO 2912-2096	2.92mm Straight Female Solder For 047SC-2901 Cable
ANO 2912-2098	2.92mm Straight Female Solder For UT-47 Cable, Solder Direct
ANO 2912-2164	2.92mm Straight Female, 2 Hole Flange Mount Solder for .086 Cable, Captivated Contact
ANO 2912-3014	2.92mm Straight Female, 4 Holes .374" SQ. Flange Launchers, Field Replaceable
ANO 2912-3019-1	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3019-2	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .012" Pin Dia, Field Replaceable

40 GHz Products



ANO 2912-3019-3	2.92mm Straight Female, 4 Holes .500" SQ. Flange Mount Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3050-1	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3050-2	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3050-3	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .015" Pin Dia, Field Replaceable
ANO 2912-3050-4	2.92mm Straight Female, 4 Holes .374" SQ. Flange Mount Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3052-1	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3052-2	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3052-3	2.92mm Straight Female, 2 Hole .551" Long Flange Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3057-1	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .009" Pin Dia., Field Replaceable
ANO 2912-3057-2	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .012" Pin Dia., Field Replaceable
ANO 2912-3057-3	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .020" Pin Dia., Field Replaceable
ANO 2912-3057-4	2.92mm Female, 2 Hole .625" Long Flange Mount, Accept .015" Pin Dia., Field Replaceable
ANO 2912-3062-1	2.92mm Female 2 Hole .500" Long Flange Accepts .009" Pin Dia, Field Replaceable
ANO 2912-3062-2	2.92mm Female 2 Hole .500" Long Flange Accepts .012" Pin Dia, Field Replaceable
ANO 2912-3062-3	2.92mm Female 2 Hole .500" Long Flange Accepts .015" Pin Dia, Field Replaceable
ANO 2912-3062-4	2.92mm Female 2 Hole .500" Long Flange Accepts .020" Pin Dia, Field Replaceable
ANO 2912-3063	2.92mm Straight Female, 4 Hole .374" SQ. Flange Launchers
ANO 2912-3065	2.92mm Female, 4 Hole .374" SQ. Flange Mount
ANO 2912-3074	2.92mm Female, 2 Hole Flange, .480" Hole Spacing, Mount Post Contact
ANO 2912-3075	2.92mm Female, 4 Hole .500" SQ. Flange Mount Tab Contact
ANO 2912-3082	2.92mm Female, 4 Hole .500" SQ. Flange Mount Post Contact
ANO 2912-3083	2.92mm Female, 2 Hole .500" Long Flange Mount Post Contact
ANO 2912-3093	2.92mm Female, 2 Hole Flange Mount .400 Hole Spacing, Post Contact
ANO 2912-3117	2.92mm Female, 2 Hole Flange Mount Post Contact
ANO 2912-3142	2.92mm Female, 4 Hole Flange Mount Post Contact
ANO 2912-3147	2.92mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 2912-3155	2.92mm Female, 2 Hole Flange Mount Post Contact
ANO 2912-3166	2.92mm Female, 4 Hole Flange Mount, Post Contact
ANO 2912-3169	2.92mm Straight Female 2 Hole Flange Mount W/ Mouse Hole

40 GHz Products



ANO 2912-4105	2.92 Female Right Angle End Launch
ANO 2912-4133	2.92mm Female PCB Mount for .042" Board
ANO 2912-5036-1	2.92mm Straight Female Thread-In To Accept .009 Pin Dia
ANO 2912-5036-2	2.92mm Straight Female Thread-In To Accept .012 Pin Dia
ANO 2912-5036-3	2.92mm Straight Female Thread-In To Accept .020 Pin Dia
ANO 2912-5157	2.92mm Straight Female Thread-in, .406 Long, ø.037 Terminal
ANO 292-A1-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 292-A1-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 292-A2-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 292-A2-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 292-A3-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 292-A3-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 292-A4-H	2.92mm Female End Launch Connector Standard Profile, Launch Pin ø0.25 [.010]
ANO 292-A4-L	2.92mm Female End Launch Connector Low Profile, Launch Pin ø0.25 [.010]
ANO 2921-2144	2.92mm Right Angle Male Solder for PLEX-090D Cable, Captivated Contact
ANO 2921-2146	2.92mm Right Angle Male Solder for .086 Cable, Captivated Contact
ANO 2921-2150	2.92mm Right Angle Male Solder for .086 Cable, Captivated Contact
ANO 2921-2162	2.92mm Right Angle Male Solder for CXN3507 / IW1501 / PLEX-140 Cable, Captivated Contact
ANO 2921-2167	2.92mm Right Angle Male Solder for CXN3507 / IW1501 / PLEX140 Cable, Captivated Contact
ANO 4112-2020	NanoRF Pin Contact Assembly Solder for .086 Cable
ANO 4112-2026	NanoRF Pin Contact Assembly Solder for .047 Cable
ANO 4112-2026-1	NanoRF Pin Contact Assembly Solder for .047 Cable
ANO 6411-2055	NMD2.92mm Straight Male Solder For IW1501/PLEX-140 Cable
ANO 6412-2056	NMD2.92mm Straight Female Solder For IW1501/PLEX-140 Cable, Captivated Contact
ANO 9311-1094	SMP Male Bulkhead Mount For .047 Cable, Full Detent
ANO 9311-1094-1	SMP Male Bulkhead Mount For .047 Cable, Limited Detent
ANO 9311-1094-2	SMP Male Bulkhead Mount For .047 Cable, Smooth Bore
ANO 9311-1120	SMP Male Bulkhead Mount for .047 Cable, Catchers Mitt
ANO 9311-2052-1	SMP Male Full Detent, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing

40 GHz Products



ANO 9311-2052-2	SMP Male Limited Detent, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing
ANO 9311-2052-3	SMP Male Smooth Bore, 2 Hole Flange Mount For .086 S/R Cable, .283" Hole Spacing
ANO 9311-4005-1	SMP Straight Male For PCB Receptacle, Full Detent
ANO 9311-4005-2	SMP Straight Male For PCB Receptacle, Limited Detent
ANO 9311-4005-3	SMP Straight Male For PCB Receptacle, Smooth Bore
ANO 9311-4005-4	SMP Straight Male For PCB Receptacle, Cather's Mitt
ANO 9311-4006-1	SMP Straight Male For PCB Edge Mount, Full Detent
ANO 9311-4006-2	SMP Straight Male For PCB Edge Mount, Limited Detent
ANO 9311-4006-3	SMP Straight Male For PCB Edge Mount, Smooth Bore
ANO 9311-4132-1	SMP-T Straight Full Detent Male for PCB Receptacle
ANO 9311-4132-2	SMP-T Straight Limited Detent Male for PCB Receptacle
ANO 9311-4132-3	SMP-T Straight Smooth Bore Male for PCB Receptacle
ANO 9311-5016-1	SMP Straight Male Full Detent Thread-in Hermetic, .015 Contact
ANO 9311-5016-2	SMP Straight Male Limited Detent Thread-in Hermetic, .015 Contact
ANO 9311-5016-3	SMP Straight Male Smooth Bore Thread-in Hermetic, .015 Contact
ANO 9311-5023	SMP Straight Male Bulkhead Shroud Solder-In Hermetic Seal, Smooth Bore
ANO 9311-5057	SMP Straight Male Bulkhead Solder For .086 Cable
ANO 9311-5069-1	SMP Straight Full Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-2	SMP Straight Limited Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-3	SMP Straight Smooth Bore Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5069-4	SMP Straight Full Detent Male, Thread-in Receptacle
ANO 9311-5069-5	SMP Straight Limited Detent Male, Thread-in Receptacle
ANO 9311-5074	SMP Male Catchers Mitt To Straight Terminal
ANO 9311-5119-1	SMP Straight Full Detent Male Bulkhead Solder for .086 Cable
ANO 9311-5119-2	SMP Straight Limited Detent Male Bulkhead Solder for .086 Cable
ANO 9311-5119-3	SMP Straight Smooth Bore Male Bulkhead Solder for .086 Cable
ANO 9311-5129	SMP Male Full Detent, Thread-in Receptacle
ANO 9311-5137-1	SMP Straight Full Detent Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5137-2	SMP Straight Limited Detent Male, Thread-in Receptacle, Spherical Radius

40 GHz Products



ANO 9311-5137-3	SMP Straight Smooth Bore Male, Thread-in Receptacle, Spherical Radius
ANO 9311-5137-4	SMP Straight Full Detent Male, Thread-in Receptacle
ANO 9311-5137-5	SMP Straight Limited Detent Male, Thread-in Receptacle
ANO 9311-5137-6	SMP Straight Smooth Bore Male, Thread-in Receptacle
ANO 9311-6009-1	SMP Male Full Detent, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6009-2	SMP Male Limited Detent, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6009-3	SMP Male Smooth Bore, Hermetic Shroud, Half Shroud Full Body
ANO 9311-6010-1	SMP Male Full Detent Hermetic Shroud, Full Shroud Full Body
ANO 9311-6010-2	SMP Male Limited Detent Hermetic Shroud, Full Shroud Full Body
ANO 9311-6010-3	SMP Male Smooth Bore Hermetic Shroud, Full Shroud Full Body
ANO 9311-6063-1	SMP Straight Hermetic Seal Male Full Detent, Solder Type
ANO 9311-6063-2	SMP Straight Hermetic Seal Male Limited Detent, Solder Type
ANO 9311-6063-3	SMP Straight Hermetic Seal Male Smooth Bore, Solder Type
ANO 9311-6065-1	SMP Male Full Detent Hermetic Shroud, Half Shroud Full Body
ANO 9311-6065-2	SMP Male Limited Detent Hermetic Shroud, Half Shroud Full Body
ANO 9311-6065-3	SMP Male Smooth Bore Hermetic Shroud, Half Shroud Full Body
ANO 9311-6090-1	SMP Straight Hermetic Seal Male, Full Detent, Solder Type,
ANO 9311-6090-2	SMP Straight Hermetic Seal Male, Limited Detent , Solder Type,
ANO 9311-6090-3	SMP Straight Hermetic Seal Male, Smooth Bore , Solder Type
ANO 9312-2001	SMP Straight Female Solder For .086 Cable
ANO 9312-2002	SMP Straight Female Solder For .047 Cable
ANO 9312-2011	SMP Straight Female Solder For RG178 Cable
ANO 9312-2082	SMP-QT (SMP QuarterTurn) Straight Female for .086 Cable
ANO 9312-2085	SMP Straight Female Solder for .086 Cable
ANO 9312-2111	SMP Straight Female Solder for .034 Cable
ANO 9312-2114	SMP Straight Female Solder for .027 Cable
ANO 9322-2003	SMP Right Angle Female Solder For .086 Cable
ANO 9322-2004	SMP R/A Female, Solder For .047 S/R Cable
ANO 9322-2012	SMP Right Angle Female Solder For RG178 Cable

40 GHz Products



ANO 9322-2037	SMP R/A Female Solder For .141 Cable
ANO 9322-2100	SMP Right Angle Female Solder for .086 Cable
ANO 9411-3057	SSMP Male Smooth Bore 2 Hole Flange Mount for .086 Cable
ANO 9411-5008-1	SMPM Straight Male Full Detent, Thread-in With ø.012 Contact
ANO 9411-5008-2	SMPM Straight Male Smooth Bore, Thread-in With ø.012 Contact
ANO 9411-5020-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5020-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5028-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5028-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5030-1	SMPM-T Straight Male Full Detent, Launcher, (Board Edge Mount)
ANO 9411-5030-2	SMPM-T Straight Male Smooth Bore, Launcher, (Board Edge Mount)
ANO 9411-5039-1	SMPM Straight Male Edge Mount, Full Detent
ANO 9411-5039-2	SMPM Straight Male Edge Mount, Smooth Bore
ANO 9411-5055-1	SMPM-T Straight Full Detent Male, Launcher, (Board Edge Mount)
ANO 9411-5055-2	SMPM-T Straight Smooth Bore Male, Launcher, (Board Edge Mount)
ANO 9412-2005	SMPM Straight Female Solder for .086 Cable
ANO 9412-2038	VITA67.1 Plug-in Contact SMPM Straight Female for .047 Cable
ANO 9412-2044	VITA67.3 Plug-in Contact SMPM Straight Female for .086 Cable
ANO 9412-2050	VITA67.1 Plug-in Contact SMPM Straight Female for .086 Cable

ADAPTERS

Product Name	Description
ANO 291-941-1484-1	Adapter, 2.92mm Male To SMPM-T Male, Full Detent
ANO 291-941-1484-2	Adapter, 2.92mm Male To SMPM-T Male, Smooth Bore
ANO 292-932-2521	Adapter, Right Angle 2.92mm Female To SMP Female
ANO 292-941-1523-1	Adapter, 2.92mm Female To SMPM-T Male, Full Detent
ANO 292-941-1523-2	Adapter, 2.92mm Female To SMPM-T Male, Smooth Bore
ANO 931-931-1382-1	Adapter, SMP Straight Male Bulkhead To SMP Male, Full Detent
ANO 931-931-1382-2	Adapter, SMP Straight Male Bulkhead To SMP Male, Limited Detent
ANO 931-931-1382-3	Adapter, SMP Straight Male Bulkhead To SMP Male, Smooth Bore

40 GHz Products



ANO 931-931-1589-1	Adapter, SMP Straight Full Detent Male Bulkhead to SMP Full Detent Male
ANO 931-931-1589-2	Adapter, SMP Straight Limited Detent Male Bulkhead to SMP Limited Detent Male
ANO 931-931-1589-3	Adapter, SMP Straight Smooth Bore Male Bulkhead to SMP Smooth Bore Male
ANO 931-931-1589-4	Adapter, SMP Straight Limited Detent Male Bulkhead to SMP Full Detent Male
ANO 931-931-1589-5	Adapter, SMP Straight Full Detent Male Bulkhead to SMP Limited Detent Male
ANO 931-932-1559	Adapter, Right Angle SMP Male (FD)to SMP Female
ANO 932-932-1082	Adapter, SMP Female To SMP Female, L=6.45 [.254]
ANO 932-932-1252	Adapter, SMP Female To SMP Female, L=8.49 [.334]
ANO 932-932-1259	Adapter, SMP Female to SMP Female, L=6.17 [.243]
ANO 932-932-1260	Adapter, SMP Female To SMP Female, L=7.26 [.286]
ANO 932-932-1261	Adapter, SMP Female To SMP Female, L=10.03 [.395]
ANO 932-932-1264	Adapter, SMP Female to SMP Female, L=5.69 [.224]
ANO 932-932-1269	Adapter, SMP Female To SMP Female, L=14.28 [.562]
ANO 932-932-1271	Adapter, SMP Female To SMP Female, L=9.60 [.378]
ANO 932-932-1273	Adapter, SMP Female To SMP Female, L=9.40 [.370]
ANO 932-932-1274	Adapter, SMP Female To SMP Female, L=9.50 [.374]
ANO 932-932-1323	Adapter, SMP Female To SMP Female, L=22.40 [.882]
ANO 932-932-1407	Adapter, SMP Female To SMP Female, L=15.24 [.600]
ANO 932-932-1414	Adapter, SMP Female To SMP Female, L=7.00 [.276]
ANO 932-932-1465	Adapter, SMP Female To SMP Female, L=12.59 [.496]
ANO 932-932-1568	Adapter, SMP Female to SMP Female, L=14.88 [.586]
PA2229A	Precision Adapter, 2.4mm Male To 2.92mm Male
PA2229B	Precision Adapter, 2.4mm Male To 2.92mm Female
PA2229C	Precision Adapter 2.4mm Female To 2.92mm Female
PA2229CA	Precision Adapter, 2.4mm Female To 2.92mm Female, VSWR: 1.20 MAX.
PA2229D	Precision Adapter, 2.4mm Female To 2.92mm Male
PA2229E	Precision Adapter 2.4mm Female To 2.92mm Female 4 Hole Flange
PA2229J	Precision Adapter, Right Angle 2.4mm Male to 2.92mm Male
PA2229K	Precision Adapter, Right Angle 2.4mm Male to 2.92mm Female

40 GHz Products



PA2229L	Precision Adapter, Right Angle 2.4mm Female to 2.92mm Female
PA2229M	Precision Adapter, Right Angle 2.4mm Female to 2.92mm Male
PA2291C	Precision Adapter, 2.4mm Female to SSMA Female
PA2291D	Precision Adapter, 2.4mm Female to SSMA Male
PA2293C	Precison Adapter, 2.4mm Female to SMP Female
PA2929A	Precision Adapter, 2.92mm Male To 2.92mm Male
PA2929B	Precision Adapter 2.92mm Male To 2.92mm Female
PA2929C	Precision Adapter 2.92mm Female To 2.92mm Female
PA2929EA	Precision Adapter, 2.92mm Female Bulkhead To 2.92mm Female
PA2929EB	Precision Adapter, 2.92mm Bulkhead Waterproof Female to 2.92mm Female
PA2929EC	Precision Adapter, 2.92mm Bulkhead Waterproof Female to 2.92mm Female
PA2929F	Precision Adapter 2.92mm Female To 2.92mm Female 4 Hole Flange
PA2929FB	Precision Adapter, 2.92mm Female to 2.92mm Female, 2 Hole Flange
PA2929FC	Precision Adapter, 2.92mm Female to 2.92mm Female, 2 Hole Flange
PA2929J	Precision Adapter Right Angle 2.92mm Male To 2.92mm Male
PA2929K	Precision Adapter Right Angle 2.92mm Male To 2.92mm Female
PA2929L	Precision Adapter Right Angle 2.92mm Female To 2.92mm Female
PA2929S	Precision Adapter, 2.92mm Male to 2.92mm Bulkhead Female
PA2991A	Precision Adapter, 2.92mm Male To SSMA Male
PA2991B	Precision Adapter, 2.92mm Male To SSMA Female
PA2991C	Precision Adapter, 2.92mm Female To SSMA Female
PA2991D	Precision Adapter, 2.92mm Female To SSMA Male
PA2993A	Precision Adapter, 2.92mm Male to SMP Male
PA2993B	Precision Adapter, 2.92mm Male to SMP Female
PA2993C	Precision Adapter, 2.92mm Female To SMP Female
PA2993D	Precision Adapter, 2.92mm Female To SMP Male, Limited Detent
PA2994A	Precision Adapter, 2.92mm Male To SMPM Male
PA2994B	Precision Adapter, 2.92mm Male To SMPM Female
PA2994C	Precision Adapter, 2.92mm Female To SMPM Female

40 GHz Products



PA2994D	Precision Adapter, 2.92mm Female To SMPM Male
PA6229A	Precision Adapter, 1.85mm Male To 2.92mm Male
PA6229B	Precision Adapter, 1.85mm Male To 2.92mm Female
PA6229C	Precision Adapter, 1.85mm Female To 2.92mm Female
PA6229D	Precision Adapter, 1.85mm Female To 2.92mm Male
PA6422C	Precision Adapter, NMD2.92mm Female to 2.4mm Female
PA6429C	Precision Adapter, NMD2.92mm Female to 2.92mm Female
PA6429CA	Precision Adapter, NMD2.92mm Female to 2.92mm Female
PA6829C	Precision Adapter, NMD2.4mm Female To 2.92mm Female
PA6829CA	Precision Adapter, NMD2.4mm Female to 2.92 Female
PA6829D	Precision Adapter, NMD 2.4mm Female to 2.92mm Male
PA6864D	Precision Adapter, NMD2.4mm Female to NMD2.92mm Male
PA6929C	Precision Adapter, NMD1.85mm Female to 2.92mm Female
PA6929CA	Precision Adapter, NMD1.85mm Female to 2.92mm Female
PA6964D	Precision Adapter, NMD1.85mm Female to NMD2.92mm Male
PA9191A	Precision Adapter, SSMA Male to SSMA Male
PA9191B	Precision Adapter, SSMA Female to SSMA Male
PA9191C	Precision Adapter, SSMA Female to SSMA Female

CABLES

Product Name	Description
AFLEX-047	AFLEX Series Cable, AFLEX-047 with Blue FEP Jacket
AFLEX-086AF	AFLEX Series Cable, AFLEX-086AF with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
AFLEX-141AF	AFLEX Series Cable, AFLEX-141AF with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
EP135	EP Series Cable, EP135 with Blue FEP Jacket, Outer Conductor: Bonded Aluminum Foil + Silver Plated Copper
PLEX140-lite	PLEX-lite Series Cable, PLEX140-lite with eTFE Jacket
PLEX150P	PLEX Series Cable, PLEX150P With Gray FEP Jacket
SR120-LL-AP	Semi-Rigid Series Cable, ANO SR120 -LL-AP with Alloy Plated Seamless Copper Tube
SR141TP-LL	Low Loss Semi-Rigid Series Cable, SR141TP-LL
SUPO-120	SUPO Series Cable, SUPO-120 with FEP Jacket

40 GHz Products



SUPO-150	SUPO Series Cable, SUPO-150 with FEP Jacket
--------------------------	---

SUPO-150G	SUPO Series Cable, SUPO-150G with Silicone Rubber Jacket
---------------------------	--

SUPO-155B	SUPO Series Cable, SUPO-155B with FEP Jacket
---------------------------	--

CABLE ASSEMBLIES

Product Name	Description
AF086-NRP-SMPMM-12	Cable Assembly, NanoRF Pin to SMPM Male Smooth Bore Interface Fit M38999 Size 12 Insert, ANO AFLEX-086 Cable, 12 Inches
AF086-SMPMF-SMPMF-12	Cable Assembly, M38999 Size 12 Insert SMPM Female to M38999 Size 12 Insert SMPM Female, ANO AFLEX-086 Cable, 12 Inches
AF086-SMPMF-SMPMM-12	Cable Assembly, VITA67.3 Plug-in Contact SMPM Female to SMPM Male Smooth Bore Interface Fit M38999 Size 12 Insert, ANO AFLEX-086 Cable, 12 Inches
P090D-29M-SMPMTF-36	Cable Assembly, 2.92mm Straight Male to SMPM-T Straight Female, PLEX-090D, 36 Inches
PT-29F-29F-26	Cable Assembly, 2.92mm Female to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29F-29F-39	Cable Assembly, 2.92mm Female to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-18F-26	Cable Assembly, 2.92mm Male to 1.85mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-18F-39	Cable Assembly, 2.92mm Male to 1.85mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-24F-26	Cable Assembly, 2.92mm Male to 2.4mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-24F-39	Cable Assembly, 2.92mm Male to 2.4mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-29F-26	Cable Assembly, 2.92mm Male to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-29F-39	Cable Assembly, 2.92mm Male to 2.92mm Female, PT-29 (PT Series Precision Test Cables), 39 Inches
PT-29M-29M-26	Cable Assembly, 2.92mm Male to 2.92mm Male, PT-29 (PT Series Precision Test Cables), 26 Inches
PT-29M-29M-39	Cable Assembly, 2.92mm Male to 2.92mm Male, PT-29 (PT Series Precision Test Cables), 39 Inches
SR086LL-29M-29F-77MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Female, SR086LL Cable, 0.077 Meters
SR086LL-29M-29M-81MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Male, SR086LL Cable, 0.081 Meters
SR120LL-29M-29F-318MM	Cable Assembly, 2.92mm Straight Male to 2.92 Straight Female, SR120LL Cable, 0.318 Meters
SR120LL-29M-29M-215MM	Cable Assembly, 2.92mm Straight Male to 2.92mm Straight Female, SR120LL Cable, 0.215 Meters
VN-NMD18F-29F-26	Cable Assembly, NMD1.85mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD18F-29F-39	Cable Assembly, NMD1.85mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches
VN-NMD18F-29M-26	Cable Assembly, NMD1.85mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD18F-29M-39	Cable Assembly, NMD1.85mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches
VN-NMD24F-29F-26	Cable Assembly, NMD2.4mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD24F-29F-39	Cable Assembly, NMD2.4mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches

40 GHz Products



VN-NMD24F-29M-26	Cable Assembly, NMD2.4mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD24F-29M-39	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches
VN-NMD29F-29F-26	Cable Assembly, NMD2.92mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 26 Inches
VN-NMD29F-29F-39	Cable Assembly, NMD2.92mm Female to 2.92mm Female, VN-29 (VNA Test Cable), 39 Inches
VN-NMD29F-29M-26	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 26 Inches
VN-NMD29F-29M-39	Cable Assembly, NMD2.92mm Female to 2.92mm Male, VN-29 (VNA Test Cable), 39 Inches

TERMINATIONS

Product Name	Description
ANO 729-101	Coaxial Termination, 2.92mm Male, 2 Watts, DC-40GHz
ANO 729-103	Coaxial Termination With Chain 2.92mm Male, 2 Watt, DC-40GHz
ANO 729-106	Coaxial Termination, 2.92 Mm Male, 5 Watts, DC-40GHz
ANO 729-108	Coaxial Termination, 2.92 Mm Male, 10 Watts, DC-40GHz
ANO 729-110	Coaxial Termination, 2.92 mm Male, 15 Watts, DC-40GHz
ANO 729-112	Coaxial Termination, 2.92 mm Male, 20 Watts, DC-40GHz
ANO 729-114	Coaxial Termination, 2.92 mm Male, 25 Watts, DC-40GHz
ANO 729-116	Coaxial Termination, 2.92 mm Male, 30 Watts, DC-40GHz
ANO 729-118	Coaxial Termination, 2.92mm Male, 40 Watts, DC-40GHz
ANO 729-119	Coaxial Termination, 2.92mm Male, 50 Watts, DC-40GHz
ANO 729-120	Coaxial Termination, 2.92mm Male, 60 Watts, DC-40GHz
ANO 729-123	Coaxial Termination With Chain 2.92mm Male, 2 Watt, DC-40GHz
ANO 729-202	Coaxial Termination, 2.92mm Female, 2 Watts, DC-40GHz
ANO 729-207	Coaxial Termination, 2.92 mm Female, 5 Watts, DC-40GHz
ANO 729-209	Coaxial Termination, 2.92 mm Female, 10 Watts, DC-40GHz
ANO 729-211	Coaxial Termination, 2.92 mm Female, 15 Watts, DC-40GHz
ANO 729-213	Coaxial Termination, 2.92 mm Female, 20 Watts, DC-40GHz
ANO 729-215	Coaxial Termination, 2.92 mm Female, 25 Watts, DC-40GHz
ANO 729-217	Coaxial Termination, 2.92 mm Female, 30 Watts, DC-40GHz
ANO 794-104	Coaxial Termination, SMPM Male, 0.25 Watts, DC~40GHz

ANO 794-107-1	Coaxial Termination, SMPM Male, Full Detent, 0.5 Watts, DC-40 GHz
-------------------------------	---

40 GHz Products



ANO 794-107-2	Coaxial Termination, SMPM Male, Smooth Bore, 0.5 Watts, DC-40 GHz
-------------------------------	---

ANO 794-203	Coaxial Termination, SMPM Female, 0.25 Watts, DC~40GHz
-----------------------------	--

ATTENUATORS

Product Name	Description
ANO 29-0202-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0202-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 2 Watt, DC-40GHz
ANO 29-0203-01	1 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-02	2 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-03	3 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-04	4 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-05	5 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-06	6 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-07	7 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-08	8 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-09	9 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-10	10 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-15	15 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz

40 GHz Products



ANO 29-0203-20	20 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-25	25 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0203-30	30 dB Attenuator, 2.92mm Female to 2.92 Female,2 Watts, DC-40 GHz
ANO 29-0206-01	1 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-02	2 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-03	3 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-04	4 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-05	5 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-06	6 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-07	7 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-08	8 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-09	9 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-10	10 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-15	15 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-20	20 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-25	25 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0206-30	30 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0207-01	1 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-02	2 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-03	3 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-04	4 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-05	5 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-06	6 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-07	7 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-08	8 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-09	9 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-10	10 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-15	15 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-20	20 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz

40 GHz Products



ANO 29-0207-25	25 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0207-30	30 dB Attenuator, 2.92mm Male to 2.92mm Female, 2 Watts, DC-43.5 GHz
ANO 29-0208-31	31 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-32	32 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-33	33 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-34	34 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-35	35 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-36	36 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-37	37 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-38	38 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-39	39 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0208-40	40 dB Attenuator, 2.92mm Female to 2.92mm Female, 2 Watts, Bi Directional, DC-40 GHz
ANO 29-0501-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0501-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 5 Watt, DC-40GHz
ANO 29-0502-01	1 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-02	2 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-03	3 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz

40 GHz Products



ANO 29-0502-04	4 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-05	5 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-06	6 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-07	7 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-08	8 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-09	9 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-15	15 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-25	25 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0502-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 5 Watts Bi Directional, DC-40 GHz
ANO 29-0504-01	1dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-02	2dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-03	3dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-04	4dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-05	5dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-06	6dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-07	7dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-08	8dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-09	9dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-10	10dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-15	15dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-20	20dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-25	25dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-35	35dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-0504-40	40dB Attenuator, 2.92mm Male to 2.92mm Female, 5 Watts Bi Directional, DC-43.5 GHz
ANO 29-1001-01	1dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-02	2dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-03	3dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional

40 GHz Products



ANO 29-1001-04	4dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-05	5dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-06	6dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-07	7dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-08	8dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-09	9dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-10	10dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-15	15dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-20	20dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-25	25dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1001-30	30dB Attenuator 2.92mm Male To 2.92mm Female, 10 Watt, DC-40GHz, bi-directional
ANO 29-1502-10	10 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-20	20 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-30	30 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1502-40	40 dB Attenuator, 2.92mm Male to 2.92 Female, 15 Watt, DC-40 GHz
ANO 29-1504-03	3 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-04	4 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-05	5 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-06	6 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-07	7 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-08	8 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-09	9 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-10	10 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-20	20 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-30	30 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-1504-40	40 dB Attenuator, 2.92mm Female to 2.92 Female, 15 Watts, Uni-directional, DC-40 GHz
ANO 29-2001-01	1dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-02	2dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-03	3dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz

40 GHz Products



ANO 29-2001-04	4dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-05	5dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-06	6dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-07	7dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-08	8dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-09	9dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-10	10dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-15	15dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-20	20dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-25	25dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2001-30	30dB Attenuator, 2.92mm Male To 2.92mm Female, 20 Watt, DC-40GHz
ANO 29-2002-10	10 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2002-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-10	10 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2003-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 20 Watt, DC-40GHz
ANO 29-2501-20	20 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-30	30 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-40	40 dB Attenuator 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-2501-50	50 dB Attenuator, 2.92mm Male To 2.92mm Female 25 Watt, DC-40GHz
ANO 29-3001-10	10 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-20	20 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-3001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 30 Watt, DC-40GHz
ANO 29-4001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 40 Watt, DC-40GHz
ANO 29-4001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 40 Watt, DC-40GHz

40 GHz Products



ANO 29-5001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5001-40	40 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5002-50	50dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5002-60	60 dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5003-30	30dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-5003-40	40dB Attenuator, 2.92mm Male To 2.92mm Female 50 Watt, DC-40GHz
ANO 29-6001-30	30 dB Attenuator, 2.92mm Male To 2.92mm Female 60 Watt, DC-40GHz
ANO 29-6001-40	40dB Attenuator, 2.92mm Male To 2.92mm Female 60 Watt, DC-40GHz

TOOLS

Product Name	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque=8±0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12±0.48 in.lbs, Hex Size =5/16 in.
ANO TWSD-001	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9±0.04 NM [8±0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue
T29002-1	Fixed Wrench for Bulkhead 2.92mm/SMA Connectors (Hex 11mm)

ACCESSORIES

Product Name	Description
ANO 2111-6099	Cap, Male With Chain for SMA, 3.5mm, 2.92mm