



CONNECTORS

Product Name	Description
ANO 4111-2021	NanoRF Socket Contact Assembly Solder for .047 Cable
ANO 6211-2003	1.85MM Straight Male Solder For CXN3506 Cable, Captivated Contact
ANO 6211-2025	1.85mm Straight Male Solder for 047SC-2901 Cable
ANO 6211-2031	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable Captivated Contact
ANO 6211-2038	1.85mm Straight Male Solder For UT-085/UT-085C-Form Cable
ANO 6211-3010-1	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .009 Pin Dia, Field Replaceable
ANO 6211-3010-2	1.85mm Straight Male 2 Hole .551" Flange Mount, Accept .012 Pin Dia, Field Replaceable
ANO 6211-3011-1	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .009" Pin Dia, Field Replaceable
ANO 6211-3011-2	1.85mm Straight Male 2 Hole .622" Flange Mount, Accept .012" Pin Dia, Field Replaceable
ANO 6211-3012-1	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .009" Pin Dia.,Field Replaceable
ANO 6211-3012-2	1.85mm Straight Male 4 Hole .500" SQ. Flange Mount, Accept .012" Pin Dia.,Field Replaceable
ANO 6211-3044-1	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .009 Dia. Pin, Field Replaceable
ANO 6211-3044-2	1.85mm Straight Male 4 Hole .375" SQ Flange Mount, Accept .012 Dia. Pin, Field Replaceable
ANO 6212-2004	1.85mm Straight Female Solder For Cxn3506 Cable, Captivated Contact
ANO 6212-2026	1.85mm Straight Female Solder For 047SC-2901 Cable
ANO 6212-2048	1.85mm Straight Bulkhead Waterproof Female Solder for .086 Cable, Captivated Contact
ANO 6212-2052	1.85mm Straight Female Solder for .034 Cable, Solder Direct
ANO 6212-3005	1.85mm Straight Female, 2 Hole .625" SQ. Flange, Solder For .047 S/R Cable
ANO 6212-3013-1	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3013-2	1.85mm Straight Female, 4 Hole .500" SQ. Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3014-1	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3014-2	1.85mm Straight Female, 2 Hole .622" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3015-1	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3015-2	1.85mm Straight Female, 2 Hole .551" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3020-1	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .009" Pin Dia., Field Replaceable
ANO 6212-3020-2	1.85mm Straight Female, 2 Hole .500" Long Flange, Accept .012" Pin Dia., Field Replaceable
ANO 6212-3035-1	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .009 Dia. Pin, Field Replaceable

67 GHz Products



ANO 6212-3035-2	1.85mm Straight Female, 4 Hole .374 SQ. Flange, Accept .012 Dia. Pin, Field Replaceable
ANO 6212-3037	1.85mm Straight Female, 4 Hole .500 SQ. Flange, Solder For .047 S/R Cable
ANO 6212-3040	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 6212-3041	1.85mm Female Vertical Launch, 2 Hole Flange, Compression Mount
ANO 6212-3051	1.85mm Female 2 Hole Flange, Vertical Launch
ANO 621-A1-H	1.85mm Male End Launch Connector Standard Profile, Launch Pin ø0.18 [.007]
ANO 621-A1-L	1.85mm Male End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 621-A2-H	1.85mm Male End Launch Connector Standard Profile, Launch Pin ø0.13 [.005]
ANO 621-A2-L	1.85mm Male End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 622-A1-H	1.85mm Female End Launch Connector, Launch Pin ø0.18 [.007]
ANO 622-A1-L	1.85mm Female End Launch Connector Low Profile, Launch Pin ø0.18 [.007]
ANO 622-A2-H	1.85mm Female End Launch Connector, Launch Pin ø0.13 [.005]
ANO 622-A2-L	1.85mm Female End Launch Connector Low Profile, Launch Pin ø0.13 [.005]
ANO 622-C1	1.85mm Female End Launch Connector Super Small End Launch-Wide
ANO 6911-2004	NMD1.85mm Straight Male Solder For CXN3506 Cable, Captivated Contact
ANO 6912-2002	NMD1.85mm Straight Female Solder For CXN3506 Cable, Captivated Contact
ANO 7511-2002	MMCX65(MMPX) Straight Angle Male Solder for RG405/.086 Cable
ANO 7521-2001	MMCX65(MMPX) Right Angle Male Solder for RG405/.086 Cable
ANO 7811-5002-1	SMPS Straight Male Full Detent 4-Port Edge Launch
ANO 7811-5002-2	SMPS Straight Male Smooth Bore 4-Port Edge Launch
ANO 9411-1024-1	SMPM Male Full Detent Snap-in Bulkhead Mount for .047 Cable
ANO 9411-1024-2	SMPM Male Smooth Bore Snap-in Bulkhead Mount for .047 Cable
ANO 9411-2023-1	SMPM Straight Male Solder For .086 Cable, Full Detent
ANO 9411-2023-2	SMPM Straight Male Solder For .086 Cable, Smooth Bore
ANO 9411-2034-1	SMPM Straight Male Bulkhead Solder for .086 Cable, Full Detent
ANO 9411-2034-2	SMPM Straight Male Bulkhead Solder for .086 Cable, Smooth Bore
ANO 9411-2037	SMPM Male Smooth Bore Interface FIT M38999 Size 12 Insert Solder for .086 Cable
ANO 9411-2047	SMPM Straight Male Full Detent 2 Hole Flange Mount Shroud, .350" Hole Spacing
ANO 9411-2049-1	SMPM Straight Full Detent Male Bulkhead Solder for .047 Cable

67 GHz Products



ANO 9411-2049-2	SMPM Straight Smooth Bore Male Bulkhead Solder for .047 Cable
ANO 9411-4001-1	SMPM Straight Male for PCB Mount, Full Detent
ANO 9411-4001-2	SMPM Straight Male for PCB Mount, Smooth Bore
ANO 9411-5009	SMPM Straight Male Panel Mount Thread-In With ø.024 Contact
ANO 9411-5010	SMPM Straight Male Full Detent Solder-In Hermetic Shroud With ø.012 Contact, .070 Length
ANO 9411-5016-1	SMPM-T Straight Male Full Detent, Thread-In With ø.012 Contact
ANO 9411-5016-2	SMPM-T Straight Male Smooth Bore, Thread-In With ø.012 Contact
ANO 9411-5041-1	SMPM-T Straight Male For PCB Mount, Full Detent
ANO 9411-5041-2	SMPM-T Straight Male For PCB Mount, Smooth Bore
ANO 9411-5054-1	SMPM-T Straight Full Detent Male, Launcher, (Board Edge Mount)
ANO 9411-5054-2	SMPM-T Straight Smooth Bore Male, Launcher, (Board Edge Mount)
ANO 9411-6040-1	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=1.52[.06]
ANO 9411-6040-2	SMPM-T Straight Male Full Detent, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=2.28[.09]
ANO 9411-6040-3	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=1.52[.06]
ANO 9411-6040-4	SMPM-T Straight Male Smooth Bore, Solder-In Hermetic Shroud With ø.012 Contact, Contact Length=2.28[.09]
ANO 9411-6051	SMPM Straight Male Screw Type Smooth Bore
ANO 9412-2004	SMPM Straight Female Solder For .047 Cable
ANO 9412-2022	SMPM-T Straight Female Solder For .047 Cable
ANO 9412-2032	SMPM-T Straight Female Solder For .086 Cable
ANO 9412-2043	SMPM Female T-FLEX 405 Cable Fit M38999 Size 12 Insert
ANO 9412-5046	SMPM Straight Female, Panel Mount Thread-in for .020 Dia. Post
ANO 9421-5042-1	SMPM-T Right Angle Male For PCB Mount, Full Detent
ANO 9421-5042-2	SMPM-T Right Angle Male For PCB Mount, Smooth Bore
ANO 9422-2007	SMPM R/A Female Solder for .047 S/R Cable
ANO 9422-2014	SMPM R/A Female Solder For .047 S/R Cable

ADAPTERS

Product Name	Description
ANO 621-941-1524-1	Adapter, 1.85mm Male To SMPM-T Male, Full Detent
ANO 621-941-1524-2	Adapter, 1.85mm Male To SMPM-T Male, Smooth Bore

67 GHz Products



ANO 622-941-1525-1	Adapter, 1.85mm Female To SMPM-T Male Full Detent
ANO 622-941-1525-2	Adapter, 1.85mm Female To SMPM-T Male Smooth Bore
ANO 941-941-1456-1	Adapter, SMPM Male to SMPM Male, Full Detent
ANO 941-941-1456-2	Adapter, SMPM Male to SMPM Male, Smooth Bore
ANO 941-941-1512	Adatper, SMPM Male to SMPM Male
ANO 941-941-1542-1	Adapter, SMPM-T Male to SMPM-T Male, Full Detent
ANO 941-941-1542-2	Adapter, SMPM-T Male to SMPM-T Male, Smooth Bore
ANO 941-941-1546	Adapter, SMPM Male(FD) to SMPM Male(FD), Hermetic Seal
ANO 942-942-1381	Adapter, SMPM Female To SMPM Female, L=6.73 [.265]
ANO 942-942-1415	Adapter, SMPM Spring Loaded Female To SMPM Female
ANO 942-942-1526	Adapter, SMPM Female To SMPM Female, L=5.36 [.211]
ANO 942-942-1527	Adapter, SMPM Female To SMPM Female, L=12.7 [.500]
PA6262A	Precision Adapter, 1.85mm Male To 1.85mm Male
PA6262B	Precision Adapter 1.85mm Male To 1.85mm Female
PA6262C	Precision Adapter 1.85mm Female To 1.85mm Female
PA6262CA	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262E	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262EA	Precision Adapter, 1.85mm Bulkhead Female to 1.85mm Female
PA6262F	Precision Adapter, 1.85 Female to 1.85 Female 4 Hole Flange
PA6262FA	Precision Adapter, 1.85mm Female to 1.85mm Female, 2 Hole Flange
PA6262FB	Precision Adapter, 1.85mm Female to 1.85mm Female, 4 Hole Flange
PA6262J	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Male
PA6262K	Precision Adapter, Right Angle 1.85mm Male To 1.85mm Female
PA6262L	Precision Adapter, Right Angle 1.85mm Female To 1.85mm Female
PA6262S	Precision Adapter, 1.85mm Bulkhead Male to 1.85mm Female
PA6276A	Precision Adapter, 1.0mm Male to 1.85mm Male
PA6276B	Precision Adapter, 1.0mm Male to 1.85mm Female
PA6276C	Precision Adapter, 1.0mm Female to 1.85mm Female
PA6276D	Precision Adapter, 1.0mm Female to 1.85mm Male

67 GHz Products



PA6278A	Precision Adapter, SMPS Male Full Detent to 1.85mm Male
PA6278D	Precision Adapter, SMPS Male Full Detent To 1.85mm Female
PA6294A	Precision Adapter, 1.85mm Male To SMPM Male
PA6294B	Adapter, 1.85mm Male to SMPM Female
PA6294C	Adapter, 1.85mm Female to SMPM Female
PA6294D	Precision Adapter, 1.85mm Female To SMPM Male
PA6962B	Precision Adapter, NMD1.85mm Male to 1.85mm Female
PA6962C	Precision Adapter, NMD1.85mm Female to 1.85mm Female
PA6962CA	Precision Adapter, NMD1.85mm Female To 1.85mm Female
PA6962D	Precision Adapter, NMD1.85mm Female to 1.85mm Male
PA6962S	Precision Adapter, NMD1.85mm Male To 1.85mm Female,Panel Mount
PA6969B	Precision Adapter, NMD1.85mm Female to NMD1.85mm Male
PA7678D	Precision Adapter, SMPS Male Full Detent to 1.0mm Female
PA8062A	Precision Adapter, 1.35mm Male To 1.85mm Male
PA8062B	Precision Adapter, 1.35mm Female to 1.85mm Male
PA8062C	Precision Adapter, 1.35mm Female To 1.85mm Female
PA8062D	Precision Adapter, 1.35mm Male to 1.85mm Female

CABLES

Product Name	Description
SR086LL	Low Loss Semi-Rigid Series Cable, 50 Ohm, With Copper Tube
SR086TP-LL	Low Loss Semi-Rigid Series Cable, SR086TP-LL
HTC-047P	Flexible Coaxial Cable, HTC-047P with Blue FEP Jacket
MB098	MB Series Cable, MB098 With Blue FEP Jacket
PLEX090	PLEX Series Cable, PLEX090 With FEP Jacket
PLEX090-lite	PLEX-lite Series Cable, PLEX090-lite with eTFE Jacket
PLEX090DBK	PLEX Series Cable, PLEX090DBK With Black FEP Jacket
PLEX102P	PLEX Series Cable PLEX102P With FEP Jacket
PLEX102S	PLEX Series Cable, PLEX102S With Blue PUR Jacket
SR070LL-TP	Low Loss Semi-Rigid Series Cable, 50 Ohm, with Tin Plated Copper Tube

67 GHz Products



[SUPO-057P](#) SUPO Series Cable, SUPO-057P with FEP Jacket

[SUPO-059](#) SUPO Series Cable, SUPO-059 with FEP Jacket

[SUPO-090](#) SUPO Series Cable, SUPO-090 with FEP Jacket

CABLE ASSEMBLIES

Product Name	Description
047X-18F-18F-15	047X Coaxial Cable 1.85mm Female to 1.85 Female
PT-18F-18F-26	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18F-18F-39	Cable Assembly, 1.85mm Female to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
PT-18M-18F-26	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18M-18F-39	Cable Assembly, 1.85mm Male to 1.85mm Female, PT-18 (PT Series Precision Test Cables), 39 Inches
PT-18M-18M-26	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 26 Inches
PT-18M-18M-39	Cable Assembly, 1.85mm Male to 1.85mm Male, PT-18 (PT Series Precision Test Cables), 39 Inches
VN-NMD18F-18F-26	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 26 Inches
VN-NMD18F-18F-39	Cable Assembly, NMD1.85mm Female to 1.85mm Female, VN-18 (VNA Test Cable), 39 Inches
VN-NMD18F-18M-26	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 26 Inches
VN-NMD18F-18M-39	Cable Assembly, NMD1.85mm Female to 1.85mm Male, VN-18 (VNA Test Cable), 39 Inches
ANO 2211-6055	Cap Male, With Chain for 2.4mm and 1.85mm

TERMINATIONS

Product Name	Description
ANO 762-101	Coaxial Termination, 1Watt, 1.85mm Male DC-67GHz, VSWR 1.35 Max.
ANO 762-108	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67GHz, VSWR 1.30 Max.
ANO 762-111	Coaxial Termination, 1.85mm Male, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.
ANO 762-202	Coaxial Termination, 1 Watt, 1.85mm Female DC-67GHz, VSWR 1.35 Max.
ANO 762-212	Coaxial Termination, 1.85mm Female, 2 Watts, DC-67 GHz, VSWR: 1.15 MAX.

ATTENUATORS

Product Name	Description
ANO 62-0201-01	1dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-02	2dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-03	3dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz

67 GHz Products



ANO 62-0201-04	4dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-05	5dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-06	6dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-07	7dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-08	8dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-09	9dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-10	10dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-15	15dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-20	20dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-25	25dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-30	30dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0201-40	40dB Attenuator, 1.85mm Male To 1.85mm Female, 2W, DC-67GHz
ANO 62-0501-01	1 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-02	2 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-03	3 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-04	4 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-05	5 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-06	6 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-07	7 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-08	8 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-09	9 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-10	10 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-15	15 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-20	20 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-25	25 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-30	30 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz
ANO 62-0501-40	40 dB Attenuator, 1.85mm Male to 1.85mm Female, 5 Watts, DC-67 GHz

DC BLOCKS

Product Name	Description
--------------	-------------



[D62-A1](#)

DC Block on Inner Conductor 1.85mm Male to 1.85mm Female Operating From 50 MHz to 67 GHz

TOOLS

Product Name	Description
ANO TW-001	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85 mm Type Connectors, Preset Torque=8±0.32 in.lbs, Hex Size =5/16 in.
ANO TW-002	Torque Wrench for SMA/3.5 mm/2.92 mm/2.4 mm/1.85mm Type Connectors, Preset Torque= 12±0.48 in.lbs, Hex Size =5/16 in.
ANO TWSD-001	Torque Wrench in Screwdriver Type, for SMA /3.5mm /2.92mm /2.4mm /1.85mm Type Connectors, Preset Torque= 0.9±0.04 NM [8±0.32 IN.LBS], Hex Size 7.94 MM [5/16 IN.]
T21003	SMA, 3.5mm 2.92mm, 2.4mm, 1.85mm Connector-Finger Thumb Wrench Blue