

Compact Multi-Coax Quick-Turn Connector

PA-5



ANOISON ELECTRONICS LLC

United States:
PO Box 1562
Dripping Springs, Texas 78620
Toll Free: 800-537-0680
Email: info@anoison.com
web: www.anoison.com

Japan:
5F, Bashamichi DOMON Building
4-53-2, Bentendori, Naka-ku
Yokohama, Kanagawa 231-0007
Tel: +81-45-228-9352
E-Mail: toshi.sasaki@anoison.com

China:
Xing Ze Rd 9-1-3
Zhenjiang, Jiangsu
PRC 212009
Tel: +86 (511) 8889 0190
E-Mail: david.zhou@anoison.com



Plug



Jack (Receptacle)

Features & Benefits:

- Up to 5 channels in one.
- Compact size (similar as 4.3-10 connector).
- Quick-turn interface.
- Dual-security (Position Code + Position Post) assures correct coax positions.
- Working frequency to 40GHz.

Technical Data:

Electrical Data	
Impedance	50 Ohms
Frequency	DC-40 GHz
VSWR TYP. (Cable Assembly)	1,15 Max. @ DC to 6 GHz; 1,25 Max. @ 6 GHz to 10 GHz; 1,35 Max. @ 10 GHz to 20 GHz
Screening Effectiveness	≥ -90 dB @ DC to 3 GHz; ≥ 70 dB @ 3-6GHz
Isolation	≥ 90 dB @ DC to 6 GHz;
Environmental Data	
Temperature Range	-55 C to +125 C
Degree of Protection	IP 68 (@1 m, 24 hours)
Mechanical Data	
Mating cycles	≥ 100
Locking Mechanism	Quick-Turn (Bayonet)


Applications:

- Small Cell and MIMO
- DAS/In-building
- Antennas, radios and filter output
- Outdoor and Indoor


Align the 3 Red Dots

Align the 3 bayonets into the slots of coupling nut



Push Plug into Jack



Rotate the coupling nut



"Click" it's locked



Minimum Installation Density